

92
County Surveyor's Record, Douglas County, Oregon

Township 30 South, Range 3 East.
Subdivision.

CHAINS	
	$\frac{1}{4}$ $\frac{S30}{S31}$ 1928
	from which
	A Fir, 18 ins. dia., bears S.24*E., 56 lks. dist., mkd. $\frac{1}{4}$ S 31 B T.
	A Cedar, 18 ins. dia., bears N.11*W., 26 lks. dist., mkd. $\frac{1}{4}$ S 30 B T.
	Desc. 465 ft. over rocky SW. slope.
52.80	Rocky draw, drains NW.; asc. 50 ft. over NE. slope.
53.90	Rocky point, bears N.; desc. 550 ft. over NW. slope.
71.50	Wash, 10 lks. wide, course S.; asc. 110 ft. over E. slope, slide rock and cliffs.
74.60	Rock spur, bears S.; desc. 80 ft. over SW. slope.
79.00	Creek, 2 lks. wide, Course S.; asc. 215 ft. over E. slope to C. C. enter dense undergrowth.
85.97	Intersect W. bdy. of the Tp. at the closing cor. of Secs. 30 and 31, which bears N.0*13'E., 3.87 chs. dist., from the cor. of Secs. 25 and 36 only and is herinbefore described.
	Land, mountainous.
	Soil, gravelly and rocky, 4th rate.
	Timber, Fir, Pine, Cedar and Hemlock.
	Undergrowth, vine maple, small fir, pine and chinquapin.
	—————
	N.0*04'W., bet. Secs. 29 and 30.
	Over mountainous land, through heavy timber and dense undergrowth.
	Desc. 195 ft. over NE. slope
6.81	Branch, 2 lks. wide, Course NE.; continue desc.
10.35	Spring branch, 1 lk. wide, C.E.; asc. 310 ft. over S. slope.
24.00	Spur, slopes E.; desc. 285 ft. over NE. slope to
40.00	Set an iron post, 3 ft. long, 1 in. dia., 27 ins. in the ground, for $\frac{1}{4}$ sec. cor., with brass cap mkd.
	$\frac{1}{4}$ S 30 S 29 1928