

77  
County Surveyor's Record, Douglas County, Oregon

Township 30 South, Range 3 East.  
Subdivisions.

CHAINS	<p>N.89*47'E., on a random line bet. secs. 17 and 20.</p> <p>40.00 Set temp. <math>\frac{1}{4}</math> sec. cor.</p> <p>80.30 Intersect N. and S. line 2 lks. S. of the cor. of secs. 16, 17, 20, and 21.</p> <p>Thence</p> <p>S.89*46'W., on a true line.</p> <p>Over mountainous land, through medium timber and medium undergrowth.</p> <p>Asc. 890 ft. over broken SE. slope to</p> <p>40.15 Set an iron post, 3 ft. long, 1 in. diam., 18 ins. in the ground, to bed rock, and build a mound of stone, 3 ft. base, 1 ft. high, around the post, for <math>\frac{1}{4}</math> sec. cor., with brass cap marked</p> <div style="text-align: center; margin: 10px 0;"> <math display="block">\frac{1}{4} \frac{S \ 17}{S \ 20}</math> <p>1928</p> </div> <p>from which</p> <p style="padding-left: 40px;">A fir, 30 ins. diam., bears N.5*W., 30 lks. dist., marked <math>\frac{1}{4}</math> S 17 B T.</p> <p style="padding-left: 40px;">A fir, 36 ins. diam., bears S.21*W., 9 lks. dist., marked <math>\frac{1}{4}</math> S 20 B T.</p> <p>Asc. 60 ft. over E. slope.</p> <p>42.25 Ridge, bears N. and SW., desc. 300 ft. over NW. slope.</p> <p>57.80 Draw, drains NW.; asc. 65 ft. over NE. slope.</p> <p>63.40 Spur, slopes N.; desc. 170 ft. over NW. slope.</p> <p>68.85 Forest Service trail, bears N. and S.</p> <p>71.10 Spring branch, 2 lks. wide, course NW.; asc. 25 ft. over NE. slope.</p> <p>77.00 Spur, slopes N.; desc. 30 ft. over NW. slope to</p> <p>80.30 The cor. of secs. 17, 18, 19, and 20.</p> <p>Land, mountainous.</p> <p>Soil, sandy, gravelly, and rocky, 3rd rate.</p> <p>Timber, fir, pine, cedar, and hemlock.</p> <p>Undergrowth, vine maple, chinquapin, small fir, pine, and hemlock.</p>
--------	---