

71
County Surveyor's Record, Douglas County, Oregon

11123

Township 30 South, Range 3 East.

Subdivision.

CHAINS

Over mountainous land, through heavy timber and dense undergrowth.

Desc. 410 ft. over N. slope.

10.32 Creek, 3 lks. wide, course W.; asc. 245 ft. over SW. slope.

28.50 Spur, slopes NW.; desc. 280 ft. over N. slope to

40.00 Set an iron post, 3 ft. long, 1 in. dia., 30 ins. in the ground, for $\frac{1}{4}$ sec. cor., with brass cap mkd.

$\frac{1}{4}$
S 18 | S 17
1928

from which

A fir, 18 ins. dia., bears N. $53\frac{1}{2}^*$ E., 43 lks. dist., mkd. $\frac{1}{4}$ S 17 B T.

A fir, 14, ins. dia., bears S. 87^* W., 50 lks. dist., mkd. $\frac{1}{4}$ S 18 B T.

Desc. 200 ft. over N. slope.

46.84 Creek, 5 lks. wide, course NW.; asc. 420 ft. over SW. slope.

62.30 Spur, slopes NW.; desc. 380 ft. over NW. slope.

77.96 Creek, 5 lks. wide, course W. ; asc. 50 ft. over S. slope to

80.00 Set an iron post, 3 ft. long, 2 ins. dia., 30 ins. in the ground, for cor, of secs. 7, 8, 17, and 18, with brass cap mkd.

T 30 S R 3 E
S 7 | S 8
S 18 | S 17.
1928

from which

A fir, 22 ins. dia., bears N. 8^* E., 36 lks. dist., mkd. T 30 S R 3 E S 8 B T.

A fir, 26 ins. dia., bears S. 50^* E., 113 lks. dist., mkd. T 30 S R 3 E S 17 B T.

A fir, 10 ins. dia., bears S. 54^* W., 31 lks. dist., mkd. T 30 S R 3 E S 18 B T.