

County Surveyor's Record, Douglas County, Oregon

South Boundary of T. 29 S., R. 2 E.

CHAINS

T 29 S	R 2 E
S 33	S 34
S 4	S 3
T 30 S	
1923	

from which,

A fir, 26 ins. in dia., bears N.62*E., 6 lks. dist.,
marked T 29 S R 2 E S 34 B T

A fir, 36 ins. in dia., bears S.28*E., 88 lks. dist.,
marked T 30 S R 2 E S 3 B T

A fir, 12 ins. in dia., bears S.68*W., 29 lks. dist.,
marked T 30 S R 2 E S 4 B T

A fir, 14 ins. in dia., bears N.5*W., 7 lks. dist.,
marked T 29 S R 2 E S 33 B T

Land, mountainous.

Soil, clay loam, and rocky; 2nd and 3rd rate.

Timber, fir, hemlock, cedar and pine.

Undergrowth, rhododendron, vine maple, and hemlock.

West, on a true line, bet. secs. 4 and 33.

Over mountainous land, through heavy timber and dense
undergrowth.

Ascend 235 ft. over SE. slope.

11.10 Spur, slopes S. Descend 65 ft. to

15.60 Brook, 5 lks. wide, course S. Ascend 225 ft. over SE.
slope to

19.40 A trail, bears NE. and SW.

33.40 Spur, slopes S. Descend 140 ft. to

40.00 Set an iron post, 3 ft. long, 1 in. dia., 27 ins. in the
ground, for $\frac{1}{4}$ sec. cor., with brass cap marked

$\frac{1}{4}$ S 33	
$\frac{1}{4}$ S 4	
1923	

from which,

A fir, 13 ins. in dia., bears N.7*E., 47 lks. dist.,
marked $\frac{1}{4}$ S 33 B T

A fir, 6 ins. in dia., bears S.47*W., 63 lks. dist.,
marked $\frac{1}{4}$ S 4 B T

Ascend 40 ft. to