

North Bdy. of T. 32 S., R. 1 E.,
 As Surveyed by Rufus S. Moore, Deputy Surveyor
 Under Contract No. 475, dated July 3, 1883.

CHAINS

From the cor. to Tps. 31 and 32 S., Rgs. 1 and 2 E.,
 which is a post $4\frac{1}{2}$ ft. long, 5 ins. sq. in mound of
 stone marked T 31 S S 31 on NE., R 2 E S 6 on SE.,
 T 32 S S 1 on SW., R 1 E S 36 on NW., faces, with 6
 notches on each edge; from which

A laurel, 22 ins. diam., bears N.51*E., 33 lks.
 dist., marked T 31 S R 2 E S 31 B T.

A black oak, 10 ins. diam., bears S.19*E., 41 lks.
 dist., marked T 32 S R 2 E S 6 B T.

A yellow pine, 36 ins. diam., bears S.41 $\frac{1}{2}$ *W., 61
 lks. dist., marked T 32 S R 1 E S 1 B T.

A black oak, 20 ins. diam., bears N.43*W., 63 lks.
 dist., marked T 31 S R 1 E S 36 B T.

Thence I run

S.89*W. on a true line bet. secs. 1 and 36.

Va. 19*30'E.

Descend through timber.

31.00 Ravine course S.70*W.

38.25 A point about 800 ft. below Tp. cor., and enter creek
 bottom, bears N and S.

40.00 Set a basalt stone 14x12x10 ins. 10 ins. in the ground
 for $\frac{1}{4}$ sec. cor. marked $\frac{1}{4}$ on N. face; from which

A yew 9 ins. diam., bears S.55*E., 9 lks. dist.,
 marked $\frac{1}{4}$ S B T.

A fir, 9 ins. diam., bears North, 29 lks. dist.,
 marked $\frac{1}{4}$ S B T.

40.75 Elk Creek, 25 lks. wide, runs S.

41.50 Leave creek bottom and ascend steep hill bears N. and S.

70.00 A point about 700 ft. above Elk Creek and top of ridge
 bears N. and S.

Descend 50 ft., to

80.00 Set a basalt stone, 14x12x7 ins., 10 ins. in the ground
 for cor. to secs. 1, 2, 35, and 36 marked with 1 notch