

## County Surveyor's Record, Douglas County, Oregon

West Boundary of T. 31 S., R. 2 E.

CHAINS

dist., marked T 31 S R 1 E. S 25 B T.

A white fir, 8 ins. diam., bears S.25 3/4\*E., 28 lks.

dist., marked T 31 S R 2 E S 31 B T.

A red fir, 12 ins. diam., bears S.9 1/2\*W., 34 lks. dist.,

marked T 31 S R 1 E S 36 B T.

A matherone, 5 ins. diam., bears N.18\*E., 31 lks.

dist., marked T 31 S R 2 E S 30 B T.

Land, broken and mountainous.

Soil, S. part--1st. rate, N. part--2nd rate.

Heavily timbered with fir and pine.

Undergrowth, fir, vine maple and hazel.

Heavily timbered and mountainous. 80.00 chs.

July 26, 1891.

Latitude observed at this cor. is 42\*50'N.

July 26, 1891.

North bet. secs. 25 and 30.

Va. 19\*30'E.

Through heavy timber.

20.00 Enter a vine maple thicket.

27.00 Leave thicket.

37.00 A bench, about 100 ft. above sec. cor.

40.00 Set a stone for 1/4 sec. cor., 14x12x4, 9 ins. in the ground, marked 1/4 on W. face, from which,

A red fir, 16 ins. diam., bears N.69\*W., 13 lks.

dist., marked 1/4 S B T.

A white fir, 8 ins. diam., bears S.69\*E., 9 lks..

dist., marked 1/4 S B T.

42.25 A spring, 1 lk. wide, course W.

62.00 Top of a ridge.

80.00 Set a stone, 16x14x8, 12 ins. in the ground, for cor. to secs. 24, 25, 19, and 30, marked with 2 notches on S. and 4 notches on N. edge, from which,