

County Surveyor's Record, Douglas County, Oregon

Willamette Meridian through Tp. 31 South,

| CHAINS | |
|--------|---|
| | North bet. secs. 25 and 30. |
| | Descend through heavy timber and dense undergrowth. |
| 2.50 | A spring branch, 5 lks. wide. C. E.; ascend, bears E. and W. |
| | Difference bet. measurement of 40.00 chs. by two sets of chainmen is 10 lks.; position of middle point |
| | By 1st set, 40.05 |
| | By 2nd set, 39.95, |
| | the mean of which is |
| 40.00 | Set basalt stone, 12x8x8 ins., 8 ins. in ground for $\frac{1}{4}$ sec. cor., marked $\frac{1}{4}$ on W. face, from which |
| | A fir, 40 ins. diam., bears S.55*E., 27 lks. |
| | Marked $\frac{1}{4}$ S. 30, B.T. |
| | A fir, 40 ins. diam., bears S.75*W., 15 lks. |
| | Marked $\frac{1}{4}$ S. 25 B.T. |
| 40.75 | Top of ridge, 150 ft. high, bears SE. and NW.; descend. |
| 66.90 | Dry bed of stream, C. E.; ascend. |
| | Difference bet. measurement of 80.00 chs. by two sets of chainmen is 10 lks., position of middle point |
| | By 1st, set, 80.05 |
| | By 2nd set, ⁷⁹ 80 .95 |
| | the mean of which is |
| 80.00 | Set a basalt stone, 18x10x6 ins., 14 ins. in the ground for cor. of secs. 24 and 25, marked with 4 notches on N. and 2 notches on S. face, from which |
| | A fir, 30 ins. diam., bears S.75*W., 34 lks. |
| | Marked T. 31 S., R 1 W., S. 25 B.T. |
| | A fir, 12 ins. diam., bears N.50*W., 48 lks. |
| | Marked T 31 S., R 1 W., S. 24 B.T. |
| | Land, mountainous. |