

Retracement of Willamette Meridian through T. 31 S.,

CHAINS

I continue to retrace the Willamette Meridian through T. 31 S., (on E. bdy. of T. 31 S., R. 1 W.), and find each half mile to closely agree with the original record for bearing and length, and I, therefore, adopt the original record.

Dependent Resurvey of Willamette Meridian through T. 31 S.

From the closing cor. of Tps. 31 and 32 S., R. 1 W., which is a basalt stone, firmly set, 6x15x5 ins. above ground, marked with C C on W., and 6 notches on N., S., and W. face; from which

- A fir, 30 ins. diam., bears N.41*E., 28 lks. dist., marked C C T 31 S R 1 E S 31 B T. (Old BT).
- A fir, 60 ins. diam., bears S.30*W., 2 lks. dist., marked C C T 32 S R 1 W S 1 B T. (Old ET).
- A fir, 40 ins. diam., bears N.74*W., 42 lks. dist., marked C C T 31 S R 1 W S 36 P T. (Old BT).

I obliterate the marks on the bearing tree referring to T. 31 S., R. 1 E., and re-mark the stone

- 31 S on N.,
- C C R 1 W and 6 grooves on W., and
- 32 S on S. face.

North, on a true line, on E. bdy. of sec. 36.

Over mountainous land, through heavy timber and dense undergrowth.

9.62 40.00 chs. northing from the cor. of Tps. 31 and 32 S., R. 1 E., only.

Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, for $\frac{1}{4}$ sec. cor. of sec. 31 only, with brass cap marked

$\frac{1}{4}$ S31
1923

from which