

County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey of Willamette Meridian
through T. 31 S.

CHAINS

A fir, 16 ins. diam., bears N.4*E., 100 lks.
dist., marked $\frac{1}{4}$ S 31 B T.

A fir, 18 ins. diam., bears S.56*E., 54 lks.
dist., marked $\frac{1}{4}$ S 31 B T.

Asc. 70 ft. to

21.77 Ridge, bears NE. and SW.; desc. 393 ft. to $\frac{1}{4}$ sec. cor.,
over NE. slope.

34.74 Trail, bears NW. and SE.

40.00 The $\frac{1}{4}$ sec. cor. established for secs. 31 and 36, which
is a basalt stone, firmly set, 4x10x6 ins. above
ground, marked $\frac{1}{4}$ on W. face; from which

A fir, 30 ins. diam., bears N.37*E., 49 lks.
dist., marked $\frac{1}{4}$ S 31 B T. (Old BT).

A fir, 30 ins. diam., bears S.55*W., 33 lks.
dist., marked $\frac{1}{4}$ S 36 B T. (Old BT).

I now change this cor. to refer to sec. 36 only, and
obliterate the marks on the bearing tree referring to
sec. 31.

Re-mark the stone

$\frac{1}{4}$ S 36 on W. face, from which

A fir, 10 ins. diam., bears N.87*W., 36 lks.
dist., marked $\frac{1}{4}$ S 36 B T. (New BT).

49.62 Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in
the ground, for cor. of secs. 30 and 31 only, with
brass cap marked

T31S	T31S
R1W	S30
S36	S31
	R1E
	1923

from which

A fir, 28 ins. diam., bears N.59*E., 102 lks.
dist., marked T 31 S R 1 E S 30 B T.

A fir, 8 ins. diam., bears S.59*E., 81 lks.
dist., marked T 31 S R 1 E S 31 B T.