

Dependent Resurvey of Willamette Meridian  
through T. 31 S.

CHAINS

53.03 Gulch, course NE., 246 ft. below  $\frac{1}{4}$  sec. cor.  
Asc. 10 ft. over SE. slope.

54.23 Spur, slopes NE.; desc. 23 ft. over N. slope.

55.87 Spring branch, 4 lks. wide, course E.  
Asc. 118 ft. over S. slope.

61.90 Spur, slopes SE.; desc. 338 ft. over NE. slope.

80.00 The cor. of secs. 25 and 36 only, which is a basalt stone  
firmly set, 4x12x10 ins. above ground, marked with 5  
notches on N., and 1 notch on S. edge; from which  
A fir, 30 ins. diam., bears S.25\*W., 21 lks. dist.,  
marked T 31 S R 1 W S 36 B T. (Old BT.)  
A fir, 24 ins. diam., bears N.24\*W., 37 lks. dist.,  
marked T 31 S R 1 W S 25 B T. (Old BT.)

Re-mark the stone  
S 36 on SW., and  
S 25 on NW. face.

Land, mountainous.  
Soil, rocky; 4th rate.  
Timber, fir, cedar, pine, oak, and laurel.  
Undergrowth, vine maple, salal, snow brush, and buck  
brush.

North, on E. bdy. of sec. 25.  
Over mountainous land, through heavy timber and dense  
undergrowth.  
Desc. 36 ft. over NE. slope.

2.57 Spring branch, 3 lks. wide, course SE.; asc. 77 ft. over  
SW. slope, to

9.62 Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in  
the ground, for  $\frac{1}{4}$  sec. cor. of sec. 30 only, with brass  
cap marked

$\frac{1}{4}$  S30  
1923

from which