

County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey of Willamette Meridian  
through T. 31 S.

CHAINS

A fir, 16 ins. diam., bears S.56\*E., 141 lks. dist.,  
marked  $\frac{1}{4}$  S 30 B T.

A fir, 34 ins. diam., bears N.14\*E., 45 lks. dist.,  
marked  $\frac{1}{4}$  S 30 B T.

Asc. 336 ft. to

40.00 The  $\frac{1}{4}$  sec. cor. established for secs. 25 and 30, which  
is a basalt stone, firmly set, 4x8x8 ins. above ground,  
marked  $\frac{1}{4}$  on W. face; from which

A fir, 40 ins. diam., bears S.55\*E., 27 lks. dist.,  
marked  $\frac{1}{4}$  S 30 B T. (Old BT.)

A fir, 40 ins. diam., bears S.75\*W., 15 lks. dist.,  
marked  $\frac{1}{4}$  S 25 B T. (Old BT.)

I now change this cor. to refer to sec. 25 only, and  
obliterate the marks on the bearing tree referring to  
sec. 30.

Re-mark the stone

$\frac{1}{4}$  S 25 on W. face; from which

A fir, 18 ins. diam., bears N.59\*W., 37 lks. dist.,  
marked  $\frac{1}{4}$  S 25 B T. (New BT).

40.25 Divide between Rogue River and Umpqua River, bears NW.  
and SE.

Forest Service telephone line and trail, bears NW. and SE.

Desc. 122 ft. over NE. slope, to

49.62 Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in  
the ground, for cor. of secs. 19 and 30 only, with  
brass cap marked

T31S	T31S
R1W	S19
S25	S30
	R1E
	1923

from which

A hemlock, 24 ins. diam., bears N.35\*E., 41 lks.