

Dependent Resurvey of Willamette Meridian through T. 31 S.

CHAINS

dist., marked T 31 S R 1 E S 19 B T.

A yew, 12 ins. diam., bears S.58\*E., 20 lks.

dist., marked T 31 S R 1 E S 30 B T.

Desc. 216 ft. to

66.85 Dry creek bed, 10 lks. wide, course NW.; asc. 206 ft. over SW. slope.

80.00 The cor. of secs. 24 and 25 only, which is a basalt stone, firmly set, 4x10x6 ins. above ground, marked with 4 notches on N., and 2 notches on S. edge; from which

A fir, 30 ins. diam., bears S.75\*W., 34 lks.

dist., marked T 31 S R 1 W S 25 B T. (Old BT).

A fir, 12 ins. diam., bears N.50\*W., 48 lks.

dist., marked T 31 S R 1 W S 24 B T. (Old BT).

Re-mark the stone

S 25 on SW., and

S 24 on NW. face.

Land, mountainous.

Soil, rocky, 4th rate.

Timber, fir and cedar.

Undergrowth, vine maple and hazel.

North, on E. bdy. of sec. 24.

Over mountainous land, through heavy timber and dense undergrowth.

Asc. 43 ft. over SW. slope, to

9.62 Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, for  $\frac{1}{4}$  sec. cor. of sec. 19 only, with brass cap marked

$\frac{1}{4}$  S19

1923

from which

A fir, 30 ins. diam., bears N.51\*E., 24 lks. dist.,