

County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey of Willamette Meridian through T. 31 S.

CHAINS											
	<p>Marked $\frac{1}{4}$ S 19 B T.</p> <p>A fir, 25 ins. diam., bears S. 46*E., 31 lks. dist.</p> <p>Marked $\frac{1}{4}$ S 19 B T.</p>										
15.00	Spur, slopes NW.; desc. 43 ft. over NE. slope.										
40.00	<p>The $\frac{1}{4}$ sec. cor. established for secs. 19 and 24, which is a basalt stone, firmly set, 4x10x6 ins. above ground, marked $\frac{1}{4}$ on W. face; from which</p> <p>A fir, 10 ins. diam., bears N.25*E., 26 lks. dist., marked $\frac{1}{4}$ S 19 B T (old B.T.)</p> <p>The old bearing tree in sec. 24 is dead and fallen. I now change this cor. to refer to sec. 24 only, and obliterate the marks on the bearing tree referring to sec. 19.</p> <p>Re-mark the stone</p> <p>$\frac{1}{4}$ S 24 on W. face; from which</p> <p>A fir, 30 ins. diam., bears S.69*W., 73 lks. dist., marked $\frac{1}{4}$ S 24 B T (New B.T.)</p> <p>A fir, 6 ins. diam., bears N.82*W., 23 lks. dist., marked $\frac{1}{4}$ S 24 B T (New B.T.)</p> <p>Desc. 292 ft. to</p>										
49.62	<p>Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the ground, for cor. of secs. 18 and 19, only, with brass cap marked</p> <div style="text-align: center; margin: 10px 0;"> <table style="border-collapse: collapse; margin: auto;"> <tr> <td style="border-right: 1px solid black; padding: 2px;">T31S</td> <td style="padding: 2px;">T31S</td> </tr> <tr> <td style="border-right: 1px solid black; padding: 2px;">R1W</td> <td style="padding: 2px;">S18</td> </tr> <tr> <td style="border-right: 1px solid black; padding: 2px;">S24</td> <td style="padding: 2px;">S19</td> </tr> <tr> <td style="border-right: 1px solid black; padding: 2px;"></td> <td style="padding: 2px;">R1E</td> </tr> <tr> <td style="border-right: 1px solid black; padding: 2px;"></td> <td style="padding: 2px;">1923</td> </tr> </table> </div> <p>from which</p> <p>A hemlock, 12 ins. diam., bears N.21*E., 65 lks. dist., marked T 31 S R 1 E S 18 B T.</p> <p>A fir, 26 ins. diam., bears S.43*E., 49 lks. dist., marked T 31 S R 1 E S 19 B T.</p> <p>Desc. 525 ft. to</p>	T31S	T31S	R1W	S18	S24	S19		R1E		1923
T31S	T31S										
R1W	S18										
S24	S19										
	R1E										
	1923										
80.00	The cor. of secs. 13 and 24 only, which is a basalt										