

County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey of Willamette Meridian through T. 31 S.

CHAINS

32.50 Spur, slopes NW.; desc. 140 ft. over NE. slope.

40.00 The $\frac{1}{4}$ sec. cor. established for secs. 13 and 18, which is a basalt stone, firmly set, 5x10x5 ins. above ground, marked $\frac{1}{4}$ on W. face; from which

A cedar, 14 ins. diam., bears S.70*E., 23 lks. dist., marked $\frac{1}{4}$ S 18 B T (Old BT.)

The old bearing tree in sec. 13 is dead.

I now change this cor. to refer to sec. 13 only, and obliterate the marks on the bearing tree referring to sec. 18.

Re-mark the stone

$\frac{1}{4}$ S 13 on W. face; from which

A fir, 40 ins. diam., bears S.22*W., 169 lks. dist., marked $\frac{1}{4}$ S 13 B T (New BT.)

A fir, 48 ins. diam., bears N.2*W., 177 lks. dist., marked $\frac{1}{4}$ S 13 B T (New BT.)

Desc. 91 ft. to

47.50 Brook, 1 lk. wide, course W.; asc. 17 ft. to

49.62 Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the ground, for cor. of secs. 7 and 18 only, with brass cap marked

T31S	T31S
R1W	S7
S13	S18
1923	R1E

from which

A fir, 40 ins. diam., bears N.53*E., 11 lks. dist., marked T 31 S R 1 E S 7 B T.

A fir, 40 ins. diam., bears S.66*E., 84 lks. dist., marked T 31 S R 1 E S 18 B T.

Asc. 115 ft. to

80.00 The cor. of secs. 12 and 13 only, which is a basalt stone, firmly set, 5x15x6 ins. above ground, marked with 2 notches on N. and 4 notches on S. edge; from which