

County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey of Willamette Meridian through T. 31 S.

CHAINS

marked 1/4 S 12 B T (Old BT.)

I now change this cor. to refer to sec. 12 only, and obliterate the marks on the bearing tree referring to sec. 7.

Re-mark the stone

1/4 S 12 on W. face; from which


A maple, 14 ins. diam., bears S.16*W., 56 lks. dist.

marked 1/4 S 12 B T (New BT.)

Desc. 105 ft. to

43.60 Beaver Creek, 20 lks. wide, course NW.; asc. 130 ft. over S. slope.

49.62 Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the ground, for cor. of secs. 6 and 7 only, with brass cap marked



from which

A fir, 8 ins. diam., bears N.51*E., 35 lks. dist., marked T 31 S R 1 E S 6 B T.

A fir, 24 ins. diam., bears S.35*E., 55 lks. dist., marked T 31 S R 1 E S 7 B T.

Asc. 590 ft. to

80.00 The cor. of secs. 1 and 12 only, which is a basalt stone, firmly set, 5x12x8 ins. above ground, marked with 1 notch on N. and 5 notches on S. edges; from which

A fir, 12 ins. diam., bears S.19*W., 32 lks. dist., marked T 31 S R 1 W S 12 B T (Old BT.)

A fir, 30 ins. diam., bears N.40*W., 41 lks. dist., marked T 31 S R 1 W S 1 B T (Old BT.)

Re-mark the stone

S12 on SW. and

S 1 on NW. face