

County Surveyor's Record, Douglas County, Oregon  
 Dependent Resurvey of Portion of N. Bdy. of T. 32 S., R. 1 E., and  
 Survey of Portion of N. Bdy. and Subdivision of T. 31 S., R. 1 E.,  
 Executed by Fred Mensch, U. S. Cadastral Engineer,  
 Under Special Instructions, dated June 7, 1922.

CHAINS

Retracement of Portion of North Boundary  
 of T. 32 S., R. 1 E.

From the corner of Tps. 31 and 32 S., R. 1 E., on the  
 Willamette Meridian,

N.89°00'E., retracing N. bdy. of Sec. 6.

50.88 Intersect the  $\frac{1}{2}$  Sec. corner.

89.46 Fall 64 lks. S. of the corner of Secs. 5, 6, 31 and 32.  
 The bearing and length of the West half of this line is  
 N.89°00'E., 50.88 chs., and of the East half, N.88°03'  
 E., 38.59 chs.

N.89°00'E., retracing N. bdy. of Sec. 5.

40.00 Find no trace of  $\frac{1}{2}$  Sec. corner.

78.51 Fall 87 lks. N. of corner of Secs. 4, 5, 32 and 33.  
 The bearing of this line is N.89°38'E., and the  
 proportionate length of each half is 39.25 chs.

N.89°00'E., retracing N. bdy. of Sec. 4.

38.85 The  $\frac{1}{2}$  Sec. corner bears S., 44 lks. dist.

79.29 Fall 4 lks. S. of the cor. of Secs. 3, 4, 33 and 34.  
 The bearing and length of the West half of this line  
 is N.89°39'E., 38.84 chs., and of the East half,  
 N.88°19'E., 40.45 chs.

Dependent Resurvey of Portion of North  
 Boundary of T. 32 S., R. 1 E.

The cor. of Secs. 3, 4, 33 and 34, is a decayed Fir  
 post, from which (old bearing trees)

A Fir, 12 ins. diam., bears N.25°E., 50 lks.  
 dist., marked T 32 S R 1 E S 34 B T.

A Fir, 24 ins. diam., bears S.47°E., 9 lks.  
 dist., marked T 32 S R 1 E S 3 B T.

A Fir, 20 ins. diam., bears S.32°W., 26 lks.  
 dist., marked T 32 S R 1 E S 4 B T.