

Dependent Resurvey of Portion of North Boundary
of T. 32 S., R. 1 E.

CHAINS

The old N. W. bearing tree is dead and fallen.
Hereafter this corner will refer to Secs. 3 and 4 only.
In place of the decayed post, no iron post available,
set a Basalt stone, 20x12x6 ins., 15 ins. in the ground,
for cor. of Secs. 3 and 4 only, marked with 3 notches
on E and W edges, S 3 on SE and S 4 on SW face.

I obliterate marks on former NE bearing tree.

Thence

S.88°19'W., on N. bdy. of Sec. 4.

Over mountainous land, through scattering timber and
dense undergrowth.

Ascend 185 ft. on E. slope.

4.00 Spur, slopes NE; thence over N. slope.

7.22 Set an iron post, 3 ft. long, 2 ins. diam., 27 ins. in
the ground, for cor. of Secs. 33 and 34 only, T. 31
S., R. 1 E., with brass cap marked

T31S	R1E
S33	S34
T32S R1E	
S4	
1923	

from which

A Pine, 60 ins. diam., bears N.22°E., 69 lks.
dist., marked T 31 S R 1 E S 34 B T.

A Fir, 12 ins. diam., bears N.69°W., 42 lks.
dist., marked T 31 S R 1 E S 33 B T.

Ascend 240 ft. on NE slope.

25.50 Head of draw, opens NE; ascend 310 ft. on SE. slope.

36.45 Ridge, divide bet. Elkhorn and Hawk Creeks, bears NW.
and SE; thence over S. slope.

40.45 The 1/2 Sec. cor. established for Secs. 4 and 33, which is
a Basalt stone, 5x10x6 ins. above ground, firmly set,
instead of a post as reported, marked 1/2 on N. face.
Hereafter this cor. will refer to Sec. 4 only. I oblit-
erate marks on N. face of stone and mark 1/2 S 4 on S.