

Dependent Resurvey of Portion of North Boundary
of T. 32 S., R. 1 E.

CHAINS

face, from which

A Sugar Pine, 12 ins. diam., bears N.15*E., 12 lks. dist., marked $\frac{1}{2}$ S B T (old B T). I obliterate the marks on this old bearing tree.

A Madrona, 12 ins. diam., bears S.36*E., 19 lks. dist., which I re-mark $\frac{1}{2}$ S 4 B T (old B T).

A Fir, 20 ins. diam., bears S.77*W., 28 lks. dist., marked $\frac{1}{2}$ S 4 B T (new B T).

Thence S.89*39'W.

Descend 350 ft. on SW. slope.

6.78 Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, for $\frac{1}{2}$ Sec. cor. of Secs. 33 only, T. 31 S., R. 1 E., with brass cap marked

$\frac{1}{2}$ S33
1923

from which

A Fir, 18 ins. diam., bears N.5*E., 35 lks. dist., marked $\frac{1}{2}$ S 33 B T.

A Fir, 15 ins. diam., bears N.19*W., 61 lks. dist., marked $\frac{1}{2}$ S 33 B T.

14.00 Dry ravine, course SW; ascend 220 ft. on SE. slope.

21.85 Spur, slopes SE; descend 140 ft. on SW. slope.

28.85 Draw, opens SW; ascend 75 ft. on SE. slope, to

38.84 The corner established for Secs. 4, 5, 32 and 33, which is a Basalt stone, 5x12x6 ins. above ground, firmly set, marked with 4 notches on E. and 1 notch on W. edge, witnessed as described in the field notes, except for discrepancy in bearing of the SE. bearing tree.

Hereafter this corner will refer to Secs. 4 and 5 only.

I mark the stone S 4 on SE. and S 5 on SW. face, obliterate marks on old bearing trees referring to Secs. 32 and 33 and re-mark the trees referring to Secs. 4 and 5.

From the corner

A Madrona, 12 ins. diam., bears S.88*E., 9 lks. dist.,