

Dependent Resurvey of Portion of North Boundary
of T. 32 S., R. 1 E.

CHAINS

1/4 S5
1923

from which

A hemlock, 16 ins. diam., bears S.31*E., 27 lks.
dist., marked 1/4 S 5 B T.

A hemlock, 26 ins. diam., bears S.88*W., 83 lks.
dist., marked 1/4 S 5 B T.

39.95 Spur, slopes N.; descend 30 ft. on NW. slope.

45.35 Creek, 2 lks. wide, course NE.; ascend 270 ft. on NE.
slope.

47.94 Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in.
the ground, for 1/4 sec. cor. of sec. 32 only, T 31 S.,
R 1 E., with brass cap marked

1/4 S32
1923

from which

A hemlock, 10 ins. diam., bears N.9*E., 35 lks.
dist., marked 1/4 S 32 B T.

A hemlock, 10 ins. diam., bears N.33*W., 45 lks.
dist., marked 1/4 S 32 B T.

54.00 Rocky spur, slopes N.; descend 140 ft. on NW. slope.

56.85 Creek, 1 lk. wide, course N.; ascend 32 ft. on NE. slope.

66.00 Rocky spur, slopes N.; descend 155 ft. on NW. slope.

76.45 Hawk creek, 2 lks. wide, course NE.; ascend 50 ft. on E.
slope, to

78.50 The cor. established for secs. 5, 6, 31, and 32, which is
a decayed fir post.

Hereafter this cor. will refer to secs. 5 and 6 only.

In place of the old post, no iron post available.

Set a conglomerate stone, 20x10x6 ins. 15 ins. in the

ground, for cor. of secs. 5 and 6, marked with 5

notches on E. and 1 notch on W. edges, S 5 on SE. and

S 6 on SW. face; from which