

Dependent Resurvey of Portion of North Boundary  
of T. 32 S., R. 1 E.

CHAINS

In place of the old post, no iron post available,  
Set a conglomerate stone, 20x12x6 ins., 15 ins. in the  
ground, for  $\frac{1}{4}$  sec. cor. of sec. 6 only, marked  $\frac{1}{4}$  S 6  
on S. face; from which

A fir, 15 ins. diam., bears N.53\*E., 23 lks. dist.,  
old bearing tree on which I obliterate the marks.

A fir, 12 ins. diam., bears S.44\*E., 46 lks. dist.,  
marked  $\frac{1}{4}$  S 6 B T (New B.T.)

A fir, 10 ins. diam., bears S.48\*W., 36 lks. dist.,  
marked  $\frac{1}{4}$  S 6 B T (New B.T.)

The old bearing tree in sec. 6 is dead and fallen.

Thence S.89\*00\*W.

6.50 Telephone line, C.O.P. Co., bears NW. and SE.

10.87 Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in  
the ground, for  $\frac{1}{4}$  sec. cor. of sec. 31 only, T. 31 S.,  
R. 1 E., with brass cap marked

$\frac{1}{4}$  S31

1923

from which

A fir, 6 ins. diam., bears N.56\*E., 132 lks. dist.,  
marked  $\frac{1}{4}$  S 31 B T.

A fir, 50 ins. diam., bears N.68\*W., 130 lks. dist.,  
marked  $\frac{1}{4}$  S 31 B T.

15.70 C.O.P. Co. transmission line, bears NW. and SE.

Thence over flat top of ridge, divide bet. Pelt and  
Timber Creeks, bears NW. and SE.

25.08 Top of impassable bluff, traverse point; thence on tra-  
verse line

South, 0.89 chs.

S.27\*W., 2.76 chs. descending steep rocky ravine to  
foot of bluff.

N.50\*W., 3.99 chs.

N.23\*W., 0.77 chs. along foot of bluff to line.