

County Surveyor's Record, Douglas County, Oregon

North Boundary of T. 31 S., R. 1 E.

CHAINS

A fir, 24 ins. diam., bears N.37*W., 6 lks. dist.,
marked T 30 S R 1 E S 33 B T.

Thence

West, on a true line, bet. secs. 4 and 33.

Over mountainous land, through heavy timber and dense
undergrowth.

Descend 85 ft. on W. slope.

4.40 Dark Canyon Creek, 8 lks. wide, course N.; ascend 220 ft.
on NE. slope.

15.50 Spur, slopes NE.; descend 170 ft. on NW. slope.

29.15 Creek, 2 lks. wide, course N.; thence over broken N. slope.

34.95 Creek, 5 lks. wide, course N.; ascend 70 ft. on NE.
slope, to

40.00 Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the
ground, for $\frac{1}{4}$ sec. cor., with brass cap marked

*FD.
12/18/23
L.H. HERBSTON
U.S.P.S.
C.S. 62/15*

$\frac{1}{4}$ S 33
S 4
1923

from which

A fir, 20 ins. diam., bears N.58*E., 5 lks. dist.,
marked $\frac{1}{4}$ S 33 B T.

A fir, 26 ins. diam., bears S.1*W., 19 lks. dist.,
marked $\frac{1}{4}$ S 4 B T.

Ascend 550 ft. on NE. slope to sec. cor.

43.55 Dry bed of creek, 5 lks. wide, course NE.

80.00 Set an iron post, 3 ft. long, 2 ins. diam., 27 ins. in
the ground, for cor. of secs. 4, 5, 32, and 33, with
brass cap marked

T30S | R1E
S32 | S33
S5 | S4
T31S
1923

from which

A fir, 38 ins. diam., bears N.21*E., 7 lks. dist.,
marked T 30 S R 1 E S 33 B T.

A fir, 38 ins. diam., bears S.52*E., 22 lks. dist.,
marked T 31 S R 1 E S 4 B T.

*Trees Destroyed
Per L. HERBSTON
U.S.P.S. 12/18/23
C.S. 62/15*