

County Surveyor's Record, Douglas County, Oregon

Subdivisions of T. 31 S., R. 1 E.

CHAINS

N.0*02'W., bet. secs. 15 and 16.

Over mountainous land, through heavy timber and dense undergrowth.

Along W. slope.

- 1.90 Trail, bears NW. and SE.
 4.00 Trail, bears NW. and E.
 6.00 Begin descent of 70 ft. on NE. slope, to
 11.00 Ravine, course E.; continue over broken W. slope.
 40.00 Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, for $\frac{1}{4}$ sec. cor., with brass cap marked

$$\begin{array}{c} \frac{1}{4} \\ \text{S16} | \text{S15} \\ \hline 1923 \end{array}$$

from which

A fir, 40 ins. diam., bears S.59*E., 11 lks. dist.,
 marked $\frac{1}{4}$ S 15 B T.

A fir, 48 ins. diam., bears S.41*W., 27 lks. dist.,
 marked $\frac{1}{4}$ S 16 B T.

Ascend 550 ft. to sec. cor.

- 40.23 Enter swampy land, bears E. and W.
 41.24 Leave same, bears E. and W.
 47.93 Brook, 1 lk. wide, course SE.; ascend on SW. slope.
 58.12 Sugar Pine Ranger Station fence, bears NW. and SE.
 66.00 Trail and telephone line to Sugar Pine Ranger Station,
 bears NE. and SW.
 69.70 Enter old burn, bears E. and W.
 73.01 Brook, 1 lk. wide, course SE.; trail, bears NW. and SE.
 80.00 Set an iron post, 3 ft. long, 2 ins. diam., 27 ins. in the ground, for cor. of secs. 9, 10, 15, and 16, with brass cap marked

$$\begin{array}{c} \text{T31S} | \text{R1E} \\ \text{S9} | \text{S10} \\ \hline \text{S16} | \text{S15} \\ 1923 \end{array}$$

from which

A chinquapin, 6 ins. diam., bears N.50*E., 110 lks.