

County Surveyor's Record, Douglas County, Oregon

Subdivisions of T. 31 S., R. 1 E.

CHAINS

T31S	R1E
S29	S28
S32	S33
1923	

from which

A fir, 40 ins. diam., bears N.78*E., 8 lks. dist.,
marked T 31 S R 1 E S 28 B T.

A fir, 40 ins. diam., bears S.52*E., 25 lks. dist.,
marked T 31 S R 1 E S 33 B T.

A fir, 36 ins. diam., bears S.2*W., 62 lks. dist.,
marked T 31 S R 1 E S 32 B T.

A fir, 20 ins. diam., bears N.55*W., 43 lks. dist.,
marked T 31 S R 1 E S 29 B T.

Thence

S.0*03'E., on a true line, bet. secs. 32 and 33.

Over mountainous land, through heavy timber and dense
undergrowth.

Ascend 550. ft. on rough NE. slope.

14.96 Sharp rocky spur, slopes SE.; triangulation point "B";
line descends 150 ft. over impassable bluff on S.
slope, to

16.76 Traverse point; continue descent 80 ft. on S. slope, to

18.43 Triangulation point "D"; thence line descends 435 ft. on
S. slope, becoming precipitous toward creek, to

31.94 Pelt Creek, 10 lks. wide, in box canyon, inaccessible at
this point, course E.; line ascends 520 ft. over im-
passable bluffs on N. slope to

37.53 Triangulation point "A"; ascend 200 ft. on precipitous
N. slope, to

40.00 Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in
the ground, for $\frac{1}{4}$ sec. cor., with brass cap marked

$\frac{1}{4}$	
S32	S33
1923	

from which

A fir, 7 ins. diam., bears N.71*E., 38 lks. dist.,
marked $\frac{1}{4}$ S 33 B T.