

County Surveyor's Record, Douglas County, Oregon

Subdivisions of T. 31 S., R. 1 E.

CHAINS

Descend 50 ft. over SE. slope.

45.10 Brook, 2 lks. wide, course SW.; ascend 150 ft. to

63.30 Spur, slopes W.; descend gradually to

79.30 The cor. of secs. 4, 5, 8, and 9.

Land, mountainous.

Soil, clay loam and stony, 2nd and 3rd rate.

Timber, fir, pine, and cedar.

Undergrowth, rhododendron, vine maple, and chinquapin.

From the cor. of secs. 31 and 32, on the S. bdy. of the Tp., heretofore described.

N.0°04'W., on a random line for distance only, bet. secs. 31 and 32.

40.00 Set temp. $\frac{1}{4}$ sec. cor.

78.26 Intersect sectional correction line, 80.06 chs. W. of cor. of secs. 28, 29, 32, and 33.

At the point of intersection

Set an iron post, 3 ft. long, 2 ins. diam., 27 ins. in the ground, for cor. of secs. 29, 30, 31, and 32, with brass cap marked

| | |
|------|-----|
| T31S | R1E |
| S30 | S29 |
| S31 | S32 |
| 1923 | |

from which

A fir, 20 ins. diam., bears N.29°E., 30 lks. dist., marked T 31 S R 1 E S 29 B T.

A fir, 38 ins. diam., bears S.41°E., 38 lks. dist., marked T 31 S R 1 E S 32 B T.

A fir, 38 ins. diam., bears S.33°W., 39 lks. dist., marked T 31 S R 1 E S 31 B T.

A cedar, 24 ins. diam., bears N.54°W., 41 lks. dist., marked T 31 S R 1 E S 30 B T.

Thence

S.0°04'E., on a true line, bet. secs. 31 and 32.

Over mountainous land, through heavy timber and dense