

County Surveyor's Record, Douglas County, Oregon

North Boundary, T. 31 S., R. 2 E.

CHAINS

23 miles, 69 chs. 90 lks. of these lines are over mountainous heavily timbered land, or through dense undergrowth.

5 miles, 75 chs. and 90 lks. are retracing old Tp. line.

GENERAL DESCRIPTION

The whole of this Township is heavily timbered and mountainous being covered with small peaks and ridges between which occur small brushy valleys on bottoms along the numerous streams susceptible of cultivation if cleared of timber and brush. The Northwestern portion is now being used as grazing land for sheep and cattle. The timber is Fir, Pine and Cedar except in the Northwestern part, where there is a small area of Larch on and in the near vicinity of the Umpqua divide. There is one settler in Sec. 36 and another in the Northeastern part of the Township.

Peter Applegate,
U. S. Deputy Surveyor.

Subdivisions, T. 31 S., R. 2 E.
Same Deputy and Contract.

I then began at the cor. of secs. 35 and 36 on the South bdy. of Tp. 31 S., R. 2 E.

Thence I ran
N.0°1'W., bet. secs. 35 and 36.

Var. 19°30'E.

- 28.00 Ascending steep hill in heavy timber.
Top of a ridge; course E. and W. 700 ft. above sec. cor.
Descend.
- 40.00 A point, about 500 ft. above sec. cor. Set a post, 4 ins. sq., 3½ ft. long, 24 ins. in the ground, for ¼ sec. cor. marked ¼ S on W. face; from which
A Red Fir, 8 ins. diam., bears N.87°W., 36 lks. marked ¼ S B T.
A White Fir, 10 ins. diam., bears S.78°E., 19 lks. marked ¼ S B T.
- 63.00 A spring, on line.
- 68.75 A branch, 1 lk. wide, course NW.
- 79.75 A branch, 5 lks. wide, course NE.
- 80.00 A point, about level with cor. on Tp. line, Set a stone, 14x12x6 ins., in mound of stone on bedrock for cor.

+ 400