

Subdivisions, T. 31 S., R. 2 E.

CHAINS

Soil, 1st rate.

Timber, Fir and Pine.

Heavily timbered.

79.50 chs.
Sept. 8, 1891.

N.0°01'W., bet. secs. 25 and 26.

Var.19°26'E.

Through heavy timber.

- 1.50 A branch, 6 lks. wide, course SE. Ascend steep hill.
- 7.50 A bench, about 200 ft. above cor, ascends gently.
- 35.00 Top of a ridge, course E. and W. about 400 ft. Descend.
- 40.00 A point, about 300 ft. above cor, set a stone, 12x8x8 ins. 8 ins. in the ground, for $\frac{1}{4}$ sec. cor. marked $\frac{1}{2}$ on W. face, from which
 - A Red Fir, 24 ins. diam., bears N.67°E., 12 lks. marked $\frac{1}{4}$ S B T.
 - A Red Fir, 12 ins. diam., bears N.81 $\frac{1}{2}$ °W., 34 lks. marked $\frac{1}{2}$ S B T.
- 47.75 A branch, 6 lks. wide, course East about 250 ft. above sec. cor., Ascend.
- 58.50 Top of a ridge, course E. and W. 300 ft. above sec. cor. Descend.
- 76.50 A branch, 6 lks. wide, course East.
- 80.00 A point, about 200 ft. above last sec. cor. set a stone, 16x12x8 ins. 10 ins. in the ground, for cor. to secs. 23, 24, 25 and 26 marked with two notches on S. and 1 notch on E. edges, from which
 - A Chinquapin, 6 ins. diam., bears S.64°E., 26 lks. marked T 31 S R 2 E S 25 B T.
 - A Chinquapin, 8 ins. diam., bears N.50°E., 38 lks. marked T 31 S R 2 E S 24 B T.
 - A White Fir, 24 ins. diam., bears S.48°W., 48 lks. marked T 31 S R 2 E S 26 B T.
 - A White Fir, 6 ins. diam., bears N.43°W., 48 lks.