

11322

Dependent Resurvey, a Portion of T. 20 S., R. 6 W.

CHAINS	
	<p>A cedar, 40 ins. diam., bears N. 85° E., 21 lks. dist., showing healed blaze scribed $\frac{1}{4}$ S under 78 years' growth.</p> <p>A cedar, 40 ins. diam., bears S. 28° W., 6 lks. dist., showing healed blaze facing corner. (Record: S. 28° W., 6 lks. dist.)</p> <p>At the corner point</p> <p>Set an iron post, 3 ft. long, 1 in. diam., 30 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;"> $\frac{1}{4}$ $\frac{S\ 22}{S\ 27}$ 1950 </p> <p>from which</p> <p>A hemlock, 32 ins. diam., bears N. 7$\frac{1}{4}$° W., 82 lks. dist., mkd. $\frac{1}{4}$ S 22 BT.</p> <p>A cedar, 40 ins. diam., bears S. 44$\frac{1}{4}$° W., 9 lks. dist., (the NW. lobe of the original bearing tree), mkd. $\frac{1}{4}$ S 27 BT.</p> <hr style="width: 10%; margin: 10px auto;"/> <p>N. 85°17' W., beginning new measurement.</p> <p>Descend very slightly.</p>
0.25	Beaver Creek, 3 lks. wide, course S. 80° W.; ascend 7 ft. over S. slope.
5.30	Descend 26 ft. over SW. slope.
13.30	A dry ravine, drains SE.; ascend 6 ft. over broken S. slope.
24.90	A dry ravine, drains SW.
31.50	A dry ravine, drains S.; ascend 124 ft. over E. slope.
33.60	Slope changes to SE. slope.
37.20	Top of spur, slopes S.; descend 136 ft. over SW. slope.
42.10	A dry ravine, drains SE.; ascend 445 ft. over broken NE. slope.
49.00	Slope changes to E. slope.
52.40	Top of ridge, the divide between Siuslaw River and Smith River drainage basins, bears N. and S.; descend 47 ft. over W. slope.
54.56	<p>The cor. of secs. 21, 22, 27 and 28, determined at the intersection of old blazed lines to the N., S., and W., and the remains of the original bearing trees:</p> <p>A maple, 10 ins. diam., bears N. 25° E., 25 lks. dist., showing a healed blaze facing SW., with core decayed.</p> <p>A dogwood stump, bears S. 54° E., 18 lks. dist., badly decayed but showing an old blaze facing NW.</p> <p>A dogwood stump and stool bears N. 45° W., 5 lks. dist.</p> <p>There is no remaining evidence of the 3-inch maple in the SW. quadrant.</p> <p>At the corner point</p> <p>Set an iron post, 3 ft. long, 2 ins. diam., 30 ins. in the ground, with brass cap mkd.</p>