

11-23

Dependent Resurvey, a Portion of T. 20 S., R. 6 W.

CHAINS

T 20 S R 6 W
 S 21 | S 22
 S 28 | S 27
 1950

*See CONNECTION
 RENEWED COR. Vol. 1
 Cor. No. 38 7/2*

from which

A fir, 13 ins. diam., bears N. 48° E., 39 lks. dist.,
 mkd. T 20 S R 6 W S 22 BT.

A fir, 42 ins. diam., bears S. 86½° E., 120 lks. dist.,
 mkd. T 20 S R 6 W S 27 BT.

A fir, 60 ins. diam., bears S. 53° W., 119 lks. dist.,
 mkd. T 20 S R 6 W S 28 BT.

A fir, 24 ins. diam., bears N. 30°45' W., 53 lks. dist.,
 mkd. T 20 S R 6 W S 21 BT.

Land, mountainous.

Soil, clay and sandy loam under shallow humus.

Timber, heavy fir, cedar, hemlock, maple, dogwood, alder, madrona,
 chinquapin, yew and cascara.

Undergrowth, bracken, vinemaple, hazel, arrowwood, willow, salal,
 thimbleberry and poison oak.

From the cor. of secs. 21, 22, 27 and 28.

N. 89°30' W., bet. secs. 21 and 28.

Through heavy timber and dense undergrowth; descend 320 ft. over
 steep W. slope.

7.40 Bottom of dry canyon, course N. 20° W.; ascend 145 ft. over broken
 NE. slope.

11.80 Top of spur, slopes N. 30° W.; descend 220 ft. over steep broken W.
 slope.

16.50 Bottom of dry canyon, course N.; ascend 135 ft. over NE. slope.

20.50 Top of spur, slopes NW.; descend 248 ft. over broken W. slope.

27.40 Bottom of dry canyon, course NW.; ascend 63 ft. over NE. slope.

30.80 Top of spur, slopes NW.; descend 75 ft. over broken SW. slope.

33.10 Bottom of dry ravine, course NW.; ascend 165 ft. over NE. slope.

37.50 Top of spur, slopes N.; descend 7 ft. over NW. slope.

38.08 The ¼ sec. cor. of secs. 21 and 28, determined from the one remain-
 ing original bearing tree:

A hemlock, 25 ins. diam., bears S. 35° W., 16 lks. dist., show-
 ing a blaze facing NE., scribed BT under 78 years' overgrowth.

At the corner point

Set an iron post, 3 ft. long, 1 in. diam., 30 ins. in the ground,
 with brass cap mkd.

¼ S 21
 S 28
 1950

from which

A hemlock, 12 ins. diam., bears N. 30½° W., 30 lks. dist.,
 mkd. ¼ S 21 BT.