

County Surveyor's Record, Douglas County, Oregon

11721-A

William W. Glenn, Cadastral Surveyor

Special & Supplemental Instructions dated: May 3, 1957; July 22, 1960; & April 26, 1962.

Group # 441 Approved: May 6, 1957; July 26, 1960; & April 26, 1962.

Assignment instructions dated: May 1, 1962 - Surveyed: June 4 thru July 10, 1962.

CHAINS

Dependent Resurvey, N. Edy., T. 20 S., R. 6 W.

from which

A hemlock, 10 ins. diam., bears N. $6\frac{1}{4}^{\circ}$ E., 381 lks.
dist., mkd. T19S R6W S36 BT.

A hemlock, 30 ins. diam., bears S. $76\frac{1}{4}^{\circ}$ E., 114 lks.
dist., mkd. T20S R6W S1 PT.

A fir, 18 ins. diam., bears N. $76\frac{1}{4}^{\circ}$ W., $83\frac{1}{2}$ lks.
dist., mkd. T19S R6W S35 BT.

From this point two iron pipes, each $\frac{3}{4}$ in diam., firmly set,
protruding 4 ins. and 24 ins. above ground, bears S. $9^{\circ} 50'$ E.,
0.045 chs. dist.

Land, mountainous.

Soil, clay loam.

Timber, fir, cedar, hemlock, maple, madrone, cascara, dogwood,
pew, and alder; undergrowth, vine maple, hazel, arrowwood,
salal, Oregon grape, bracken, and sworn fern, blackberry,
poison oak, blackcap, and maiden hair fern.

Dependent Resurvey of a Portion of the
Subdivisional Lines, T. 20 S., R. 6 W.
Willamette Meridian, Oregon
(Restoring the 1872 survey by J. H. McClung)

From the $\frac{1}{4}$ sec. cor. of secs. 25 and 26, monumented with
the original sandstone, 12 x 10 x 8 ins., firmly set, 4 ins.
in the ground, marked $\frac{1}{4}$ on the W. face, alongside of
which the Douglas County Surveyor has set an iron post,
 $1\frac{1}{4}$ ins. diam., protruding 5 ins. above ground, firmly set,
with brass cap mkd.

*FD OK 4/96
Roberts
M123-60*

	SURVEYORS		O
A	T 20 S	R 6 W	F
N	$\frac{1}{4}$ S 26	S 25	F
H	1962		I
O			C
O			E

FROM which the Douglas County Surveyor's bearing trees:

A fir, 13 ins. diam., bears S. $81\frac{1}{2}^{\circ}$ E., 95 lks.
dist., mkd. $\frac{1}{4}$ S25 CS BT on double blaze.

A fir, 43 ins. diam., bears N. $86\frac{1}{2}^{\circ}$ W., 34 lks.
dist., mkd. $\frac{1}{4}$ S26 CS BT.

Add marks ELM 1962 to brass cap.

N. $2^{\circ} 24'$ E., bet. secs. 25 and 26, marking and blazing
the true line.

Descend 418 ft. over NE. slope, along E. edge of logged
area, through scattering timber and dense undergrowth.

20.96 Creek, 5 lks. wide, course NW.; asc. 340 ft. over SW. slope.

27.75 Spur, slopes SW.; desc. 12 ft. over N.W. slope.

41.06 Point for the cor. of secs. 23, 24, 25 and 26, at proportionate
distance; there is no remaining evidence of the original
corner.

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 26 ins.
in the ground, with brass cap mkd.