

# County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey, Subdivisional Lines, T. 20 S., R. 6 W.

CHAINS

T 20 S	R 6 W
S 23	S 24
S 26	S 25
1962	

from which

- A fir, 23 ins. diam., bears N.  $48\frac{1}{2}^\circ$  E., 8 lks.  
dist., mkd. T20S R6W S24 FT.
- A fir, 23 ins. diam., bears S.  $70\frac{1}{2}^\circ$  E., 41 lks.  
dist., mkd. T20S R6W S25 FT.
- A fir, 28 ins. diam., bears S.  $72\frac{3}{4}^\circ$  W.,  $21\frac{1}{2}$  lks.  
dist., mkd. T20S R6W S26 FT.
- A fir, 23 ins. diam., bears N.  $30\frac{1}{2}^\circ$  W.,  $30\frac{1}{2}$  lks.  
dist., mkd. T20S R6W S23 FT.

The cor. is located in the head of a ravine, drains S.  $70^\circ$  W.

Land, mountainous.  
Soil, clay and clay loam.  
Timber, fir, hemlock, cedar, maple, alder, chinquapin, madrone, dogwood, cascara, and willow; undergrowth, vine maple, hazel, salal, Oregon grape, arrowwood, huckleberry, blackberry, bracken, and sword fern, maiden hair fern, poison oak, thimbleberry, salmonberry, elderberry, Canadian thistle, and ceanothus.

From the cor. of secs. 19, 24, 25, and 30, on the E. bdy. of the Twp., perpetuated and recorded by the Douglas County Surveyor, in 1962, monumented with an iron post,  $1\frac{1}{4}$  ins. diam., firmly set, protruding 12 ins. above ground, with brass cap mkd.

S	SURVEYORS	O
D	T 20 S	F
D	S 24	S 19
D	S 25	S 30
U	R 6 W	R 5 W
U	1962	E

FROM which the original bearing trees:

- A fir, 43 ins. diam., bears N.  $49^\circ$  E.,  $46\frac{1}{2}$  lks.  
dist., (dist. to face, 44 lks.) with a healed blaze. (Record distance, 44 lks.)
- A fir snag, 12 ins. diam., bears S.  $65^\circ$  E., 76 lks.  
dist., with scribe marks T20S R5W S30 visible on opened blaze.
- A cedar, 35 ins. diam., bears S.  $70^\circ$  W., 42 lks.  
dist., with a healed blaze.  
(Record tree, a redwood)
- A fir, 58 ins. diam., bears N.  $72^\circ$  W., 27 lks.  
dist., with scribe marks T20S R6W S2 Visible on bark blaze. The Douglas County Surveyor has remarked this tree T20S R6W S24 DCS FT.

and Douglas County Surveyor's bearing tree

- A fir, 15 ins. diam., bears S.  $59\frac{3}{4}^\circ$  E., 125 lks.  
dist., mkd. T20S R5W S30 DCS FT.

Add marks FLM 1962 to brass cap.

S.  $88^\circ 14'$  W., bet. secs. 24 and 25.

Ascend 84 ft. over general E. slope, through heavy timber and dense undergrowth.