

County Surveyor's Record, Douglas County, Oregon

147240

Dependent Resurvey, Subdivisional Lines, T. 20 S., R. 6 W.

CHAINS

- 6.00 Spur, slopes N. 30° E.; desc. 205 ft. over NW. slope.
- 15.68 Creek, 1 lk. wide, course N. 15° E.; asc. 80 ft. over NE. slope.
- 23.88 Creek, 1 lk. wide, course N. 40° E.; asc. 282 ft. over E. slope.
- 39.74 Point for the $\frac{1}{4}$ sec. cor. of secs. 24 and 25, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.

T 20 S R 6 W
 $\frac{1}{4}$ S 24
 S 25
 1962

from which

A fir, 18 ins. diam., bears N. 5° E., 31 lks. dist., mkd. $\frac{1}{4}$ S24 BT.

A fir, 20 ins. diam., bears S. 44° W., $31\frac{1}{2}$ lks. dist., mkd. $\frac{1}{4}$ S25 BT.

Ascend 4 ft. over E. slope.

- 40.50 Junction of spurs, sloping N. and W.; desc. 155 ft. over W. slope, along top of spur.

- 59.61 Point for the $\frac{1}{16}$ sec. cor. of secs. 24 and 25.

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.

W $\frac{1}{16}$ S 24
 S 25
 1962

from which

A fir, 38 ins. diam., bears N. 38° W., 22 lks. dist., mkd. W $\frac{1}{16}$ S24 BT.

A fir, 36 ins. diam., bears S. 81 $\frac{1}{2}$ ° W., 21 lks. dist., mkd. W $\frac{1}{16}$ S25 BT.

Descend 37 ft. over W. slope.

- 69.00 Leave top of spur, slopes S. 80° W., turning N. 40° W.

- 71.48 Ravine, drains N; asc. 29 ft. over NE. slope.

- 73.85 Spur, slopes N. 40° W.; desc. 143 ft. over W. slope.

- 79.48 The cor. of secs. 23, 24, 25 and 26.

Land, mountainous.
 Soil, clay loam.
 Timber, fir, hemlock, cedar, maple, madrone, chinquapin, dogwood, and yew; undergrowth, vine maple, hazel, arrowwood, salal, Oregon grape, bracken, and sword fern, blackberry, and poison oak.

~~N. 1° 13' W., bet. secs. 23 and 24.~~

~~Ascend 56 ft. over SW. slope, through heavy timber and light undergrowth.~~