

# County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey, Subdivisional Lines, T. 20 S., R. 6 W.

CHAINS

40.68

The cor. of secs. 1, 2, 35, and 36, on the N. bdy. of the Twp.

Land, mountainous.  
Soil, clay and clay loam.  
Timber fir, hemlock, cedar, maple, madrone, ash, dogwood, alder, cascara, chinquapin, and yew; undergrowth, vine maple, hazel, salal, arrowwood, poison oak, blackberry, Oregon grape, huckleberry, salmonberry, bracken, and sword fern.

From the cor. of secs. 23, 24, 25 and 26.

N. 89° 45' W., bet. secs. 23 and 26.

Descend 359 ft. over SW. slope through heavy timber and light undergrowth.

2.00 Leave timber, enter logged area, edge bears NW. and S.

12.73 Smith Creek, 10 lks. wide, course N.; asc. 425 ft. over E. slope, changing to NE. slope.

13.00 Dirt road, 15 lks. wide, bears N. and S.

34.75 Spur, slopes N. 10° E.; desc. 157 ft. over NW. slope.

39.80 Point for the  $\frac{1}{4}$  sec. cor. of secs. 23 and 26, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 28 ins. long, 2 $\frac{1}{2}$  ins. diam., 24 ins. in the ground, with brass cap mkd.

T 20 S R 6 W

$\frac{1}{4}$  S 23  
S 26

1962

from which

A fir, 14 ins. diam., bears N. 30 $\frac{1}{2}$ ° W., 56 $\frac{1}{2}$  lks. dist., mkd.  $\frac{1}{4}$  S23 BT.

A cedar, 10 ins. diam., bears S. 66 $\frac{1}{2}$ ° W., 82 lks. dist., mkd.  $\frac{1}{4}$  S26 BT.

Descend 172 ft. over NW. slope.

40.05 Leave logged area, enter heavy timber, edge bears N. 80° E. and S.

45.60 Creek, 2 lks. wide, course N. 15° E.; asc. 407 ft. over NE. slope.

55.22 Spur, slopes N. 30° E.; also leave heavy timber, enter old logged area, edge bears W. and S.; desc. 36 ft. over NW. slope.

57.72 Ravine, drains N.; asc. 98 ft. over NE. slope.

61.10 Spur, slopes N. 10° E.; desc. 261 ft. over NW. slope.

67.00 Ravine, drains N. 10° E.; asc. 510 ft. over general E. slope.

79.60 The cor. of secs. 22, 23, 26 and 27, which is monumented with an iron post, 2 ins. diam., protruding 7 ins. above ground, firmly set, with brass cap, marked and witnessed as described in the official record.

The cor. is located on the ridge dividing Siuslaw River and Smith River drainages, ridge bears NW. and S. 20° E.

E O N  
D F O T E S