

Field Notes of the Dependent Resurvey of Part of the South Boundry Part of the East Boundry, Part of the West Boundry and Part of the Subdivisional Lines of T. 20 S., R. 8 W., W. M., Oregon, Executed by Thomas A. Tillman, Cadastral Engineer under Special Instructions dated April 13, 1950, Group 292; Survey commenced June 8, 1950; Survey Completed Oct. 10, 1950.

CHAINS

Dependent Resurvey of a Portion of the S. Bdy, of T. 20 S., R. 18 W., (Restoring the 1883 survey of William P. Wright)

The cor. of Tps. 20 and 21 S., R. 8 W., on the W. bdy. of T. 21 S., R. 7 W., is determined from the original bearing trees as follow:

An uprooted hemlock, 8 ins. diam., the stumphole of which bears S. 29° W., 14 lks. dist., nearly rotted away.

A maple, 28 ins. diam., bears N. 75° W., 39 lks. dist., with axe marks visible at top of blaze, the remainder covered by a fir log.

At the corner point.

Set an iron post, 3 ft. long, 3 ins. diam., 28 ins. in the ground, with brass cap marked

T 20 S	T 21 S
R 8 W	
S 36	R 7 W
S 1	
T 21 S	S 6
1950	

from which new bearing trees

A cedar, 40 ins. diam., bears S. 77½° W., 29 lks. dist., marked T21S R8W S1 BT.

A fir, 60 ins. diam., bears N. 43° W., 93 lks. dist., marked T20S R8W S36 BT.

N. 88° 41' W., bet. secs. 1 and 36, marking and blazing the true line.

Descend 26 ft. over W. slope, through heavy timber and dense undergrowth.

0.60 Clabber Creek, 6 lks. wide, course S. 5° E.; asc. 643 ft. over steep E. slope, changing to broken NE. slope.

16.05 A spur,, slopes SE.; desc. 27 ft. along broken S. Slope.

24.55 The head of a ravine, course S. 20° E.; asc. 180 ft. over E. slope, changing to SE. slope.

30.00 Top of ascent on S. slope; desc. 180 ft. over SW. slope.

39.23 Point for the ¼ sec. cor. of secs. 1 and 36, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, with brass cap marked

¼ S 36
S 1
1950

from which

A fir, 46 ins. diam., bears N. 63° 45' W., 43 lks. dist., marked ¼ S36 BT.

A Fir, 20 ins. diam., bears S. 64½° W., 40 lks. dist., marked ¼ S1 BT.

Descend 176 ft. over SW. slope.

51.85 A branch, 1 lk. wide, course S. 40° W.; asc. 12 ft. over SE. slope.

52.95 Top of ascent on S. slope; desc. 153 ft. over SW. slope.

57.35 A branch, 1 lk. wide, course SW.; asc. 5 ft. over SE. slope.

58.00 Top of ascent on S. slope; desc. 87 ft. over SW. slope.

61.75 A branch, 3 lks. wide, course S. 30° E.; asc. 340 ft. over NE. slope.

67.85 A spur, slopes S. 40° E.; desc. 100 ft. over SW. slope.