

County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey of a Portion of the East Boundary of T. 20 S., R. 8 W.

CHAINS

A fir, 66 ins. diam., bears West, 26 lks. dist., with partial scribe marks visible on the bark. (Record, 25 lks. dist.)

At the corner point

Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, with brass cap marked

1/4 S 36

1950

from which new bearing trees

A hemlock, 12 ins. diam., bears S. 37 1/4° W., 41 lks. dist., marked 1/4 S36 BT.

A fir, 12 ins. diam., bears N. 28° W., 127 lks. dist., Marked 1/4 S36 BT.

N. 1° 08' E., beginning new measurement.

Ascend 47 ft. over SW. slope.

3.50 Top of ascent on W. slope; desc. 41 ft. over NW slope.

4.75 A branch, 1 lk. wide, course W.; asc. 93 ft. over broken SW. slope.

14.85 Top of ascent on W. slope; desc. 43 ft. over NW slope.

17.50 A branch, 4 lks. wide, course S. 60° W.; asc. 133 ft. over SW. slope.

~~26.60~~

26.60 A spring branch, 1 lk. wide, course SW.; asc. 208 ft. over SW slope.

40.99 The cor. of secs. 25 and 36, determined at the record bearing from the original SW. bearing tree and the record bearing and distance from the original NW. bearing tree as follows:

A fir, 40 ins. diam., bears S. 17° W., 63 lks. dist., plainly blazed and healed. (Record, 73 lks. dist.)

A maple, 22 ins. diam., bears N. 77° W., 12 lks. dist., plainly blazed and healed. (Wright's record, 72 lks. dist.; Todd's record, 12 lks. dist.)

At the corner point

Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the ground, with brass cap marked

T 20 S | T 20 S

S 25

S 36 | R 7 W

R 8 W | S 31

1950

from which a new bearing tree

A hemlock, 10 ins. diam., bears N. 12 1/2° W., 67 lks. dist., marked T20S R8W S25 BT.

Land, mountainous.

Soil, sandy clay loam.

Timber, fir, hemlock, cedar, maple, alder, chinquapin, dogwood, madrona and cascara.

Undergrowth, vine maple, hazel, evergreen huckleberry, red huckleberry, slickleaf, arrowwood and salal.

N. 1° 04' E., along E. bdy. of sec. 25.