

Dependent Resurvey of a Portion of the East
Boundary of T. 20 S., R. 8 W.

CHAINS	
	Ascend 165 ft. over SW. slope, through heavy timber and dense undergrowth.
7.45	A ridge, at E. side of saddle, the divide bet. Clabber Creek and Hardenbrook Creek, bears NW. and SE.; desc. 95 ft. over N. slope.
9.45	The head of a ravine, course NE.; desc. 155 ft. along E. slope, changing to NE. slope.
15.80	A ravine, at forks from N. 70°W. and S. 70°W., course S. 80°E.; asc. 74 ft. over SE. slope.
17.73	The closing cor. of secs. 30 and 31, T. 20 S., R. 7 W., bears West, 2 lks. dist., monumented with a wooden post, 3 ins. square, 4 ft. above ground, firmly set, marked T20S R7W S30 and S31 with a lumber crayon, from which A fir, 40 ins. diam., bears N. 3¼°E., 226 lks. dist., with the scribe marks T20S R7W visible on the opened blaze. (There is no record of this bearing tree, but a count of annual growth rings dates the blaze at 1891.) A stuphole, from which a fir, 48 ins. diam., has slid down the hill, bears N. 20°E., 18 lks. dist., with the blaze covered by earth and rocks. (Agrees with Todd's record) A fir, 32 ins. diam., bears S. 33°E., 25 lks. dist., plainly blazed and healed. (Record bearing, S. 57°E.) A dead fir, 18 ins. diam., bears N. 85°W., 32 lks. dist., with partial scribe marks visible on the partly opened blaze. (Record bearing, N. 82°W.) A sandstone in place, 20 x 20 x 4 ins. above ground, bears N. 80°W., 6 lks. dist., with the chiseled marks WC plainly visible. (Agrees with Todd's record.) Ascend 155 ft. over SE. slope, changing to S. slope.
20.95	A spur ridge, at W. side of saddle, bears N. 80°E. and S. 80°W.; desc. 230 ft. over N. slope.
25.20	A ravine, course N. 80°E.; asc. 150 ft. over SE. slope.
29.10	Top of ascent on E. slope; desc. 17 ft. over NE. slope.
30.05	The head of a ravine, course E.; asc. 104 ft. over SE. slope.
33.50	A blazed and graded trail, bears NE. and SW.
33.90	A ridge, the divide bet. Hardenbrook Creek and South Sister Creek bears N. 70°E. and S. 60°W.; desc. 217 ft. over broken NW. slope.
39.85	Point for the ¼ sec. cor. of sec. 25 at proportionate distance; there is no remaining evidence of the original corner. Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground with brass cap marked. ¼ S 25 1950 from which A fir, 42 ins. diam., bears S. 85½°W., 62 lks. dist., marked ¼ S25 BT.