

Dependent Resurvey of a Portion of the East Boundary
of T. 20 S., R. 8 W.

CHAINS	
	A fir, 50 ins. diam., bears N.70 $\frac{1}{2}$ °W., 136 lks dist., marked $\frac{1}{4}$ S25 BT.
	Descend 130 ft. over broken NW. slope.
42.30	The head of a ravine, course N.70°W.; asc. 13 ft. along W. slope.
45.00	Top of ascent on W. slope; desc. 180 ft. over NW. slope.
50.90	A ravine, course N.70°W.; asc. 59 ft. along broken west slope.
57.60	Top of ascent on W. slope; desc. 272 ft. over broken NW. slope.
69.20 69.50	An intermittent branch, 4 lks. wide, course N. from S. 20°W.; desc. 16 ft. along branch.
74.35	Leave branch, course N.20°W.; asc. 15 ft. along W. slope.
76.70	Top of ascent on W. slope; desc. 25 ft. over NW. slope.
79.70	The cor. of secs. 24 and 25, determined at the record bearing from the original SW. bearing trees and the record bearing and distance from the original NW. bearing tree as follows: A fir, 56 ins. diam., bears S.71°W., 81 lks. dist., plainly blazed and healed. (Record, 77lks. dist.) A dead fir, 36 ins. diam., bears N.47°W., 71 lks. dist., with partial scribe marks visible on the bark. At the corner point Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the ground, with brass cap marked <div style="text-align: center;"> T 20 S T 20 S S 24 ---S 25--- R 7 W R 8 W S 30 1950 </div> from which a new bearing tree A fir, 60 ins. diam., bears N. 55°W., 126 lks. dist., marked T20S R8W S24 BT. Land, mountainous. Soil, rocky clay. Timber, fir, hemlock, cedar, maple, alder, dogwood, and yew. Undergrowth, vine maple, salmonberry, thimbleberry, devil's club, hazel, salal, and slickleaf.
Dependent resurvey of a portion of the W. Bdy. of T. 20 S., R. 8 W. (Restoring the 1883 survey of William P. Wright and the 1893 survey of Alonzo Gesner.)	
The cor. of Tps. 20 and 21 S., R. 8 W., on the E. bdy. of T. 21 S., R. 9 W., is monumented with an iron post. 3 ins. diam., 7 ins. above ground, firmly set, marked and witnessed as described in the official record.	
From this point, Scare Creek Lookout, bears S. 14° 56' W., approximately 33.00 chs. dist.	
N. 1° 27' E., along the W. bdy. of sec. 31, marking and blazing the true line.	
Ascend 129 ft. over S. slope, through heavy timber and dense undergrowth.	