

11336 County Surveyor's Record, Douglas County, Oregon

12

Dependent Resurvey of a Portion of the Subdivisional Lines of T. 20 S., R. 8 W. (Restoring the 1884 survey of William P. Wright)

CHAINS									
	<p>A fir, 16 ins. diam., bears S.70°W., 22 lks. dist., marked $\frac{1}{4}$ S35 BT.</p> <p>Descend 200 ft. over N. slope.</p>								
48.50	A ravine, course N.60°E.; asc. 100 ft. over SE. slope.								
52.50	Top of ascent on E. slope; desc. 190 ft. over NE. slope.								
59.50	A ravine, at forks from N.25°W. and S.80°W., course S.65°E.; asc. 340 ft. over S. slope.								
70.00	A spur ridge, bears S.65°E. and N.60°W.; desc. 100 ft. over NE. slope.								
71.20	A ravine, course S. 65°E.; asc. 185 ft. over SE. slope.								
78.00	A blazed and graded trail, bears N.60°E. and S.60°W.								
78.10	A ridge, the divide bet. Devils Club Creek and Clabber Creek, bears N.60°E. and S.60°W.; desc. 258 ft. over N. slope.								
83.99	<p>Point for the cor. of secs. 25, 26, 35, and 36, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the ground, with brass cap marked</p> <div style="text-align: center;"> <table border="1"> <tr> <td>T 20 S</td> <td>R 8 W</td> </tr> <tr> <td>S 26</td> <td>S 25</td> </tr> <tr> <td>S 35</td> <td>S 36</td> </tr> <tr> <td colspan="2">1950</td> </tr> </table> </div> <p>from which</p> <ul style="list-style-type: none"> A fir, 54 ins. diam., bears N.78°E., 104 lks. dist., marked T20S R8W S25 BT. A hemlock, 8 ins. diam., bears S.47°45'E., 84 lks. dist., marked T20S R8W S36 BT. A hemlock, 8 ins. diam., bears S.65°45'W., 21 lks. dist., marked T20S R8W S35 BT. A fir, 54 ins. diam., bears N.83½°W., 94 lks. dist., marked T20S R8W S26 BT. <p>Land, mountainous. Soil, rocky clay. Timber, fir, hemlock, cedar, maple, alder, chinquapin, madrona, and yew. Undergrowth, vine maple, hazel, slickleaf, manzanita, arrowwood, and salal.</p>	T 20 S	R 8 W	S 26	S 25	S 35	S 36	1950	
T 20 S	R 8 W								
S 26	S 25								
S 35	S 36								
1950									
	<p>From the cor. of secs. 25 and 36, on the E. bdy. of the Tp.</p> <p>N. 84° 10'W., bet. secs. 25 and 36.</p> <p>Descend 380 ft. over broken SW. slope, through heavy timber and dense undergrowth.</p>								
28.75	Clabber Creek, 5 lks. wide, course S.25°E.; asc. 400 ft. over E. slope, changing to N. slope.								
38.52	<p>Point for the $\frac{1}{4}$ sec. cor. of secs. 25 and 36, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set an iron post, 3 ft. long, 1 in., diam., 28 ins. in the ground, with brass cap marked</p> <div style="text-align: center;"> <table border="1"> <tr> <td>$\frac{1}{4}$ S 25</td> </tr> <tr> <td>S 36</td> </tr> <tr> <td>1950</td> </tr> </table> </div>	$\frac{1}{4}$ S 25	S 36	1950					
$\frac{1}{4}$ S 25									
S 36									
1950									