

Dependent Resurvey of a Portion of the Subdivisional
Lines of T. 20 S., R. 8 W.

| CHAINS | |
|--------|---|
| 16.45 | A ravine, course SW.; asc. 125 ft. over broken SW. slope. |
| 20.15 | A sharp spur, slopes S.80°W.; desc. 81 ft. over NW. slope. |
| 22.55 | A ravine, course W.; asc. 235 ft. over SW. slope. |
| 29.10 | A spur ridge, at E. side of saddle, bears N.80°W. and S.80°E.; desc. 399 ft. over NW. slope. |
| 38.40 | A branch, 1 lk. wide, course N. 20°E.; asc. 25 ft. along E. slope. |
| 41.00 | Top of ascent on E. slope; desc. 11 ft. over NE. slope. |
| 41.48 | Point for the $\frac{1}{4}$ sec. cor. of secs. 26 and 27, at proportionate distance; there is no remaining evidence of the original corner. Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, with brass cap marked <div style="text-align: center;"> $\frac{1}{4}$ S 27 S 26 1950 </div> from which A fir, 50 ins. diam., bears S.5°E., 40 lks. dist., marked $\frac{1}{4}$ S26 BT. A cedar, 36 ins. diam., bears S.80°W., 68 lks. dist., marked $\frac{1}{4}$ S27 BT. Descend 79 ft. over NE. slope. |
| 43.10 | A branch, 4 lks. wide, course N.80°W.; asc. 100 ft. over broken SW. slope. |
| 47.55 | A branch, 1 lk. wide, course SW.; asc. 145 ft. over broken SW. slope. |
| 50.35 | A spur, slopes SW.; desc. 20 ft. along W. slope. |
| 56.55 | A branch, 1 lk. wide, course S.40°W.; asc. 415 ft. over broken S. Slope. |
| 71.20 | A broad spur, slopes S.65°W.; desc. 100 ft. over NW. slope. |
| 79.00 | Bottom of descent on W. slope; asc. 40 ft. over SW. slope. |
| 82.96 | The cor. of secs. 22, 23, 26, and 27, determined at the point of intersection of original blazed lines, duly identified. At the corner point Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the ground, with brass cap marked <div style="text-align: center;"> T 20 S R 8 W S 22 S 23 ———— S 27 S 26 1950 </div> from which A fir, 12 ins. diam., bears N.85 $\frac{1}{2}$ °E., 22 lks. dist., marked T20S R8W S23 BT. A fir, 18 ins. diam., bears S.70°W., 42 lks. dist., S.66 $\frac{1}{2}$ °E., 17 lks., marked T20S R8W S27 BT. A fir, 50 ins. diam., bears S.7°W., 43 lks. dist., marked T20S R8W S27 BT. |