


11348 County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey of a Portion of the Subdivisional Lines of T. 20 S., R. 8 W.

CHAINS

At the corner point

Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, with brass cap marked



from which new bearing trees

A fir, 38 ins. diam., bears S.31°E., 43 lks. dist., marked $\frac{1}{4}$ S 27 BT.

A fir, 24 ins. diam., bears N.37°W., 59 lks. dist., marked $\frac{1}{4}$ S28 BT.

The $\frac{1}{4}$ sec. cor. is located at the top of an ascent on a gradual W. slope.

N. 2° 02' W., beginning new measurement.

Descend 30 ft. over gentle NW. slope, changing to NE. slope.

4.35 A branch, 2 lks. wide, course N.30°W.; asc. 65 ft. over SW. slope.

8.85 Top of ascent of W. slope; desc. 151 ft. along precipitous W. slope, changing to NW. slope.

24.35 Right bank of Smith River, 120 lks. wide, 1 to 3 ft. deep at summer stage, flowing on sandstone bedrock bottom, with frequent potholes, course N.12°E.

29.20 Left bank of Smith River; asc. 140 ft. over SE. slope.


35.40 A spur ridge, and a blazed trail, bears N.70°E. and S.70°W.; desc. 146 ft. over N. slope.

38.50 Edge of bottom, bears N.75°E. and S.75°W.; thence across bottom.

39.93 The cor. of secs. 21, 22, 27, and 28, located at the point of intersection of original blazed lines, duly identified.

at the corner point

Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the ground, with brass cap marked



from which

An alder, 24 ins. diam., bears N.45°E., 123 lks. dist., marked T20S R8W S22 BT.

An alder, 20 ins. diam., bears S.46°E., 82 lks. dist., marked T20S R8W S 27 BT.

A hemlock, 12 ins. diam., bears S.31°W., 81 lks. dist., marked T20S R8 W S28 BT.

A cedar, 42 ins. diam., bears N.83 $\frac{1}{2}$ °W., 70 lks. dist., marked T20S R8W S21 BT.

Land, mountainous and rolling.

Soil, sandy clay loam.

Timber, fir, hamlowk, cedar, maple, alder cascara, yew madona.