

Dependent Resurvey of a Portion of the
Subdivisional Lines of T. 20 S., R. 8 W.

CHAINS

S.47°E., 7 lks. dist., with the scribe marks BT S33 T visible on the opened blaze.

A fir, 28 ins. diam., bears S.63°W., 29 lks. dist., plainly blazed and healed.

At the corner point

Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the ground, with brass cap marked

T 20	S	R 8	W
S 29	S	S 28	
S 32	S	S 33	
1950			

from which new bearing trees

A fir, 16 ins. diam., bears S.65½°E., 35 lks. dist., marked T 20S R8W S33 BT.

A fir, 16 ins. diam., bears N.21½°W., 40 lks. dist., marked T20S R8W S29 BT.

Land, mountainous.

Soil, sandy clay loam.

Timber, fir, hemlock, cedar, maple, alder, cascara, chinquapin, yew, madrona, and dogwood.

Undergrowth, vine maple, salmonberry, evergreen huckleberry, red huckleberry, salal, hazel, thimbleberry, and devil's-club.

From the cor. of secs. 27, 28, 33, and 34.

S. 87° 57' W., bet. secs. 28 and 33.

Descend 437 ft. along broken S. slope, changing to W. slope, through heavy timber and dense undergrowth.

41.50 Edge of bottom, bears N.10°W. and S.20°E.; desc. 5 ft. across bottom.

41.90 A blazed and graded trail, bears N.15°W. and S.15°E.

43.35 Point for the ¼ sec. cor. of secs. 28 and 33, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, with brass cap marked

¼	S 28
	S 33
1950	

from which

A fir, 48 ins. diam., bears N.66½°W., 25 lks. dist., marked ¼ S28 BT.

A fir, 48 ins. diam., bears S.20°E., 6¼ lks. dist., marked ¼ S33 BT.

Descend 14 ft. across bottom land.

48.15 Right bank of Smith River, 120 lks. wide, course N.20°E.

49.40 Left bank of Smith River; asc. 320 ft. over broken E. slope, changing to NE. slope.

63.50 A broad spur, slopes S.80°E. from NW.; desc. 41 ft. over SW. slope.

69.80 A branch, 1 lk. wide, course S.15°E.; asc. 80 ft. over E. slope,