

11374

Dependent Resurvey of Part of the South Boundary of
T. 21 S., R. 8 W.

CHAINS

The geographic position of this township corner is lat. 43° 41' 36" N., and long. 123° 42' 16" W.

Thence

N. 87° 53' E., on S. bdy. of sec. 31.

Asc. 158 ft. over broken NW. slope, through heavy dead timber and dense undergrowth.

2.30 Head of branch, 2 lks. wide, course NW.

8.90 A spur ridge, bears NE. and SW.; enter heavy green timber, bears NE. and SW.; desc. 95 ft. over SE. slope.

12.95 Head of ravine, course S.; asc. 34 ft. over SW. slope.

20.00 A spur, slopes SE.; desc. 151 ft. over NE. slope.

23.70 A branch, 5 lks. wide, course SE.; asc. 26 ft. over SW. slope.

27.50 A spur, slopes SW.; desc. 17 ft. over SE. slope.

28.40 A ravine, course S.; asc. 145 ft. over SW. slope.

39.79 Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, for witness cor. to the 1/4 sec. cor. of sec. 6 only, with brass cap mkd.

WC 1/4 S 6
1945

from which

A fir, 32 ins. diam., bears S. 36 1/2° E., 27 lks. dist., mkd. W C 1/4 S 6 B T.

A fir, 28 ins. diam., bears S. 68° W., 94 lks. dist., mkd. W C 1/4 S 6 B T.

39.89 The 1/4 sec. cor. of sec. 6 only, a white fir, 20 ins. diam., mkd. on bark 1/4 S on S. side. I re-blaze and re-mark 1/4 S 6 on S. side. (No accessories)

Thence

N. 88° 44' E., with new measurement.

Asc. 94 ft. over SW. slope.

5.70 A spur ridge, bears NW. and S. 75° E.; desc. 43 ft. over NE. slope.

8.10 Foot of descent on N. slope; asc. 22 ft. over NW. slope.

11.10 A spur, slopes NE.; desc. 349 ft. over broken NE. slope.

16.70 A spring branch, 2 lks. wide, course NE.

18.46 Proportional measurement.

Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, for 1/4 sec. cor. of sec. 31 only, with brass cap mkd.

1/4 S 31
1945

from which

A fir, 38 ins. diam., bears N. 30° E., 227 lks. dist., mkd. 1/4 S 31 B T.