

Dependent Resurvey of Part of the South Boundary of
T. 21 S., R. 8 W.

CHAINS
39.98

The 1/4 sec. cor. of sec. 33 only the locus of which is determined at the record measurement from each of the old bearing trees.

At point for corner,

Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, for 1/4 sec. cor. of sec. 33 only, with brass cap mkd.

FD OK
Les Roberts
M 12A-44
2-10-97

1/4 S 33

1945

from which

A fir, 40 ins. diam., bears N. 80° W., 240 lks. dist., mkd. on bark 1/4 S B T. I re-blaze and re-mark this old bearing tree 1/4 S 33 B T.

A stump hole bears S. 80 1/4° W., 187 lks. dist., which is the position of the old SW. bearing tree.

A fir, 16 ins. diam., bears N. 65 1/4° W., 259 lks. dist., mkd. 1/4 S 33 B T. (New B.T.)

Thence

East, with new measurement.

Asc. 50 ft. over SW. slope.

4.52 A trail, bears N. 20° W. and S. 20° E.

4.90 Ridge, divide bet. Cedar Creek and Umpqua River, bears N. 20° W. and S. 20° E.; desc. 70 ft. over broken NE. slope.

8.80 A spur, slopes NE.; desc. 169 ft. over SE. slope.

16.30 A ravine, course NE.; asc. 2 ft. over NW. slope.

17.30 Top of ascent on N. slope; desc. 136 ft. over NE. slope, changing to SE. slope.

23.45 A branch, 3 lks. wide, course NE.; asc. 65 ft. over NW. slope.

25.65 A point on line from which the closing corner of secs. 3 and 4, T. 22 S., R. 8 W., determined by reference to the record measurement from each of the old bearing trees, bears South, 8 lks. dist.

At original point for closing corner,

Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the ground, for closing cor. of secs. 3 and 4, with brass cap mkd.

T 21 S R 8 W

S 33

S 4 | S 3

C C

T 22 S R 8 W

1945

from which

A fir, 32 ins. diam., bears S. 11 1/4° E., 26 lks. dist., mkd. on bark S 4 T 22 S R 8 W. I re-blaze and re-mark this old bearing tree T 22 S R 8 W S 3 C C B T.

A fir, 52 ins. diam., bears S. 62° W., 38 lks. dist., with blaze healed. (Old B.T.)

Asc. 57 ft. over NW. slope.

28.00 A spur, slopes N.; desc. 123 ft. over broken NE. slope.