

Dependent Resurvey of the W. Bdy. of T. 21 S., R. 8 W.

CHAINS

- 27.60 A spur, slopes E.; desc. 12 ft. over NE. slope.
- 29.00 A ravine, course SE.; asc. 350 ft. over broken S. slope.
- 35.50 A spur, slopes S. 70° E.; desc. 124 ft. over NE. slope.
- 38.99 Proportional measurement.

Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, for  $\frac{1}{4}$  sec. cor. of sec. 6 only, with brass cap mkd.

|  $\frac{1}{4}$  S 6

1945

from which

A cedar, 30 ins. diam., bears N. 88° E., 146 lks. dist., mkd.  $\frac{1}{4}$  S 6 B T.

A fir, 28 ins. diam., bears S. 35 $\frac{1}{2}$ ° E., 122 lks. dist., mkd.  $\frac{1}{4}$  S 6 B T.

Desc. 82 ft. over NE. slope.

- 39.80 A ravine, course E.; asc. 180 ft. over SE. slope.
- 43.80 A spur, slopes E.; desc. 202 ft. over NE. slope.
- 47.80 A ravine, course E.; asc. 222 ft. over SE. slope.
- 52.40 A spur ridge, bears E. and W.; desc. 440 ft. over NE. slope.
- 60.60 A ravine, course E.; asc. 107 ft. over SE. slope.
- 65.10 A spur, slopes E.; desc. 185 ft. over NE. slope.
- 68.80 A branch, 1 lk. wide, course S. 80° E.; asc. 427 ft. over broken S. slope.
- 77.98 The cor. of Tps. 20 and 21 S., R. 8 W., the locus of which is determined at the record bearing and distance from the original NW. bearing tree.

At point for corner,

Set an iron post, 3 ft. long, 3 ins. diam., 28 ins. in the ground, for cor. of Tps. 20 and 21 S., Rs. 8 W., with brass cap mkd.

	T 20 S
	R 8 W
T 21 S	S 31
R 9 W	S 6
S 1	T 21 S

1945

from which

A fir, 46 ins. diam., bears N. 61° W., 28 lks. dist., the surface scar on the tree, its kind and position agree with the official record; I do not uncover the marks.

A fir, 36 ins. diam., bears N. 56 $\frac{1}{2}$ ° E., 84 lks. dist., mkd. T 20 S R 8 W S 31 B T. (New B.T.)

A fir, 30 ins. diam., bears S. 74° E., 95 lks. dist., mkd. T 21 S R 8 W S 6 B T. (New B.T.)

Land, mountainous.

Soil, loose sandy loam, 1st and 2nd rate.

Timber, fir, hemlock, cedar, alder, maple, chinquapin, madrona, yew and cascara.