

Dependent Resurvey of Part of the Subdivision of  
T. 21 S., R. 8 W.

CHAINS

1.30 Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the ground, for witness cor. to the cor. of secs. 28, 29, 32 and 33, with brass cap mkd.

W C	
T 21 S R 8 W	
S 29	S 28
-----	
S 32	S 33
1945	

from which

A fir, 44 ins. diam., bears N. 1° 45' E., 165 lks. dist., mkd. W C T 21 S R 8 W S 28 B T.

A fir, 44 ins. diam., bears S. 31° E., 106 lks. dist., mkd. W C T 21 S R 8 W S 28 B T.

A dead fir, 28 ins. diam., bears S. 39° W., 70 lks. dist., mkd. W C T 21 S R 8 W S 29 B T.

A fir, 44 ins. diam., bears N. 0° 45' W., 271 lks. dist., mkd. W C T 21 S R 8 W S 29 B T.

6.20 A spur, slopes E.; desc. 170 ft. over NE. slope, changing to NW. slope.

12.60 A ravine, course NE.; asc. 48 ft. over SE. slope.

17.50 A spur, slopes N. 70° E.; desc. 111 ft. over NE. slope.

21.50 A ravine, course N. 70° E.; asc. 29 ft. over SE. slope.

23.30 A spur, slopes E.; desc. 62 ft. over NE. slope.

26.70 A branch, 10 lks. wide, course SE.; asc. 360 ft. over SW. slope.

37.815 Proportional measurement.

Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, for  $\frac{1}{4}$  sec. cor., with brass cap mkd.

$\frac{1}{4}$	
S 29	S 28
-----	
1945	

from which

A fir, 52 ins. diam., bears N. 76° E., 128 lks. dist., mkd.  $\frac{1}{4}$  S 28 B T.

A dead fir, 60 ins. diam., bears N. 56° W., 172 lks. dist., mkd.  $\frac{1}{4}$  S 29 B T.

Asc. 52 ft. over SW. slope.

39.20 A spur, slopes S. 75° W.; desc. 49 ft. over broken W. slope.

44.60 A shallow ravine, course S. 75° W.; asc. 11 ft. over SW. slope.

45.70 A spur, slopes W.; desc. 111 ft. over NW. slope.

50.00 A ravine, course SW.; asc. 273 ft. over broken SW. slope.

66.60 A ravine, course SW.; asc. 341 ft. over broken SE. slope, changing to S. slope.

75.63 Proportional measurement.

Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the ground, for cor. of secs. 20, 21, 28 and 29, with brass cap mkd.