


Dependent Resurvey of Part of the Subdivision of
T. 21 S., R. 8 W.

CHAINS

- 3.95 A branch, 2 lks. wide, course SW.; asc. 117 ft. over S. slope, changing to SW. slope.
- 11.60 A spur, slopes W.; desc. 139 ft. over NW. slope.
- 16.50 A branch, 4 lks. wide, course W.; asc. 158 ft. over SW. slope.
- 25.20 A spur, slopes SW.; desc. 12 ft. over NW. slope.
- 27.20 Foot of descent on W. slope; asc. 92 ft. over SW. slope.
- 37.60 A spur, slopes W.; desc. 22 ft. over NW. slope.
- 39.04 Proportional measurement.

Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, for $\frac{1}{4}$ sec. cor., with brass cap mkd.



from which


A fir, 40 ins. diam., bears S. 33° E., 15 lks. dist., mkd. $\frac{1}{4}$ S 29 B T.

A fir, 48 ins. diam., bears S. 53 $\frac{1}{2}$ ° W., 166 lks. dist., mkd. $\frac{1}{4}$ S 30 B T.

Desc. 32 ft. over NW. slope.

- 41.40 Foot of descent on W. slope; asc. 126 ft. over SW. slope.
- 58.00 A spur, slopes W.; desc. 126 ft. over NW. slope.
- 63.70 A branch, 1 lk. wide, course S. 75° W.; asc. 113 ft. over SW. slope.
- 68.80 A poor logging road, bears NW. and SE.
- 71.00 A ridge, divide between Smith River and Umpqua River, bears NW. and SE.; desc. 235 ft. over broken NE. slope.
- 75.50 A shallow wet ravine, course NE.
- 76.10 A shallow wet ravine, course NE.
- 78.08 Proportional measurement.

Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the ground, for cor. of secs. 19, 20, 29 and 30, with brass cap mkd.



from which

A dead fir, 28 ins. diam., bears N. 72° E., 72 lks. dist., mkd. T 21 S R 8 W S 20 B T.

A dead cedar, 32 ins. diam., bears S. 34 $\frac{1}{2}$ ° E., 276 lks. dist., mkd. T 21 S R 8 W S 29 B T.

A dead fir, 66 ins. diam., bears S. 22° W., 253 lks. dist., mkd. T 21 S R 8 W S 30 B T.

A dead fir, 64 ins. diam., bears N. 21 $\frac{1}{2}$ ° W., 83 lks. dist., mkd. T 21 S R 8 W S 19 B T.