

Dependent Resurvey of a Portion of Subdivision of T 22 S., R. 10 W.

CHAINS	<p>"Reestablishment of surveys executed by W. H. Byars, U. S. Deputy Surveyor, in 1874 and by Aurelius Todd, U. S. Deputy Surveyor, in 1894."</p>
	<p>The cor. of secs. 27 and 28 only, on the S bdy. of sec. 22; lat. 43° 38' 15" N., longitude 123° 52' 45" W., is a stone in place, 20x16x8 ins. mkd. and witnessed as described in the official record.</p>
	<p>Thence</p>
	<p>West, retracing N. bdy. of sec. 28.</p>
15.90	<p>Fall 27 lks. N. of closing cor. of secs. 21 and 22.</p>
39.81	<p>Fall 68 lks. N. of $\frac{1}{4}$ sec. cor. of sec. 28 only.</p>
	<p>Offset to $\frac{1}{4}$ sec. cor. and commence new measurement.</p>
39.32 $\frac{1}{2}$	<p>Fall 19 lks. S of cor. of secs. 28 and 29 only.</p>
	<p>Thence</p>
	<p>West, retracing N. bdy. of sec. 29.</p>
16.05 $\frac{1}{2}$	<p>Fall 8 lks. S. of closing cor. of secs. 20-21.</p>
39.33 $\frac{1}{2}$	<p>Fall 19 lks. S. of $\frac{1}{4}$ sec. cor. of sec. 29 only.</p>
	<p>The $\frac{1}{4}$ sec. cor. of sec. 29 only is a rock in place, 6 x 5 ft., 4 ft. above ground, mkd. and witnessed as described in the official record. The bearing trees are both dead.</p>
	<p>from the cor.</p>
	<p>A fir, 12 ins. diam., bears S 71° 00' E., 6 lks. dist., mkd. $\frac{1}{4}$ S 29 B T. (New B.T.)</p>
	<p>A fir, 10 ins. diam., bears S. 87° 00' E., 28 lks. dist., mkd. $\frac{1}{4}$ S 29 B T. (New B.T.)</p>
	<p>I cut the marks from the old bearing tree which is north of line.</p>
	<p>Thence</p>
	<p>S 89° 43' E., on true line, on N. bdy. of sec. 29.</p>
	<p>Desc. 120 ft. over NE. slope, through scattering timber and dense undergrowth.</p>
3.20	<p>Stream, 1 lk. wide, course N 60° W; asc. 500 ft. over SW slope changing to NW slope.</p>
11.50	<p>Ridge, bears N 20° W and S; leave scattering and enter heavy timber, bears N and S. Desc. 225 ft. over NE. slope.</p>
18.25	<p>Draw, course NE1 continue descent 200 ft. over NE. slope.</p>
23.28	<p>The closing cor. of secs. 20 and 21, hereinafter described.</p>
	<p>Desc. 575 ft. over NE. slope changing to nearly E. slope.</p>
35.20	<p>Leuder Creek, 10 lks. wide, course N 30° W; asc. 100 ft. over broken W slope.</p>
39.33 $\frac{1}{2}$	<p>The point for cor. of secs. 28 and 29 only, which is recovered from the SE bearing tree. The record gives the cor. point as marked on a stone in place, 24x20x6 ins. above ground, but no stone in place was to be found in that vicinity.</p>
	<p>At point for cor.</p>
	<p>Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the ground, for cor. of secs. 28 and 29 only, with brass cap marked</p>