

Dependent Resurvey of a Portion of Subdivision of T 22 S, R 10 W.

CHAINS 6.94	Spur, slopes NW; desc. 25 ft. over SW slope.
11.79	Head of a draw, course S 80° W; asc. 100 ft. over NW slope.
13.44	Spur, slopes W; desc. 25 ft. over SW slope.
16.14	Foot of descent on W slope; asc. 170 ft. over NW slope.
21.89½	Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground for N 1/16 sec. cor., with brass cap mkd.  <div style="text-align: center;"> <p>N 1/16 S 21   S 22 1936</p> </div> <p style="text-align: right;">from which</p> <p>A fir, 10 ins. diam., bears N 68°30' E 18 lks. dist., marked N 1/16 S 22 B T.</p> <p>A fir, 12 ins. diam., bears S 72°00' W, 15 lks. dist., marked N 1/16 S 21 B T.</p> <p>Asc. 100 ft. over NW slope.</p>
24.59	Spur, slopes NE; desc. 150 ft. over SE slope.
30.09	Stream, 1 lk. wide, course S 70° E.
33.24	Stream, 4 lks. wide, course NE; asc. 100 ft. over NW slope.
40.19	Stream, 2 lks. wide, course N 20° W; continue ascent 30 ft. over NE slope.
4 3.79	The ¼ sec. cor., which is a hemlock tree, 8 ins. in the ground, with brass cap mkd.  <div style="text-align: center;"> <p>¼ S 21   S 22 1936</p> </div> <p style="text-align: right;">* dia. mkd. ¼ S. on West side. Set an iron post, 3 ft long 1 in. diam. 28 ins.</p> <p>A fir, 24 ins. diam., bears S 80°30' E, 67 lks. dist., mkd. ¼ S 22 B T (New B.T.)</p> <p>A dead fir, 8 ins. diam., bears S 19°00' E, 12 lks. dist., mkd. ¼ S (Old B.T.)</p> <p>A fir, 34 ins. diam., bears S 71°00' W., 36 lks. dist., mkd. ¼ S 21 B T. (New B.T.)</p> <p>A dead alder, 8 ins. diam., bears S 13°00' W, 26 lks. dist., with a decayed blaze. (Old B.T.)</p> <p>Thence</p> <p>S 0° 58' W, with new measurement.</p> <p>Ascend 70 ft. over NE slope.</p>
5.08	Ridge, bears N 70° E, and S 70° W; desc. 100 ft. over gentle SE slope.
19.10	Stream, 2 lks. wide, course S 60° E; asc. 70 ft. over NE. slope.
22.10	Ridge, bears N 80° W and S 80° E; desc. 195 ft. over S slope changing to SE slope.