

Segregation Survey of Power Project No. 605
 Sec. 21, T 22 S, R 10 W.

CHAINS

A fir, 12 ins. diam., bears N 47° 30' W, 38 lks. dist. mkd.
 A P 3 P P 605 B T.

From this point the N 1/16 cor. of secs. 21 and 22 bears S 88°
 53' E 8.98 chs. dist.


Thence

N 88° 53' W, along E and W center line of NE quarter of sec. 21 and
 S bdy. of Power Project No. 605.

Desc. 110 ft. over NW slope, through heavy timber and dense under-
 growth.

2.90 Creek, 5 lks. wide, course N 20° E; asc. 20 ft. over E slope.

3.36 Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, for
 angle point No. 4, Power Project No. 605, with brass cap mkd.



from which

A hemlock, 40 ins. diam., bears N 43° 00' E, 65 lks. dist., mkd.
 A P 4 P P 605 B T.

A fir, 15 ins. diam., bears S 47° 30' E 17 lks. dist., mkd.
 T 22 S R 10 W S 21 B T.


From this point the NE 1/16 sec. cor. of sec. 21 bears N 88° 53' W
 8.23 chs. dist.

Thence

N 16° 15' E, along W bdy of Power Project No. 605.

Along E slope, through heavy timber and scattering undergrowth.

2.35 Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, for
 angle point No. 5, Power Project No. 605, with brass cap mkd.



from which

A fir, 10 ins. diam., bears N 82° 30' E, 38 lks. dist., mkd.
 A P 5 P P 605 B T.


A fir, 18 ins. diam., bears S 58° 30' W, 64 lks. dist., mkd.
 T 22 S R 10 W S 21 B T.

Thence

N 56° 30' E, along W bdy. of Power Project No. 605.

Desc. 45 ft. over NE slope, through heavy timber and scattering
 underbrush.

0.96 Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, for
 witness point No. 6, Power Project No. 605, with brass cap mkd.



from which