

DEPENDENT RESURVEY, PORTION OF N. BDY., T. 24 S., R. 3 W.

CHAINS

Set an iron post, 3 ft. long, 3 ins. diam., 28 ins. in the ground and in a circular mound of stone, 4 ft. base, to top, with the original stone deposited at the base, with brass cap mkd.

	T 23 S
	R 3 W
	<u>S 31</u>
T 24 S	R 4 W
	S 1
	1950

from which

A fir, 30 ins. diam., bears N. 21° E., 266 lks. dist.,  
mkd. T 23 S R 3 W S 31 BT.

A fir, 60 ins. diam., bears N. 63°45' E., 257 lks. dist.,  
mkd. T 23 S R 3 W S 31 BT.

From this corner the closing corner of Tps. 23 and 24 S., R. 4 W., bears North, 4.71 chs. dist.; the closing corner (on the verge of obliteration) is determined from the remains of the original bearing trees:

A stumphole, bears N. 16° W., 9 lks. dist.

A stumphole, bears S. 40° W., 52 lks. dist.

At the corner point

Set an iron post, 3 ft. long, 3 ins. diam., 28 ins. in the ground, with brass cap mkd.

	T 23 S	T 23 S
	R 4 W	
	<u>S 36</u>	S 31
CC	S 1	
	T 24 S	R 3 W
		1950

from which

A cedar, 9 ins. diam., bears N. 32°45' W., 101 lks. dist.,  
mkd. T 23 S R 4 W S 36 CC BT.

A fir, 36 ins. diam., bears S. 77½° W., 182 lks. dist.,  
mkd. T 24 S R 4 W S 1 CC BT.

S. 89°55' E., along the S. bdy. of sec. 31, T. 23 S., R. 3 W.

Descend 20 ft. along top of small spur, slopes E., through heavy timber and dense undergrowth in logged and burned area.

- 3.60 The proportionate position for the closing cor. of Tps. 24 S., Rs. 3 and 4 W.; continue to descend 21 ft. on small spur, slopes E.
- 5.22 A branch, 3 lks. wide, course SE.; continue to descend 37 ft. along a broken S. slope.
- 10.55 A spring branch, 1 lk. wide, course S.
- 11.85 A branch, 2 lks. wide, course S. 20° W.; ascend 63 ft. along broken S. slope.
- 23.40 A spring branch, 3 lks. wide, course S. 20° W.
- 25.65 A spring branch, 2 lks. wide, course SE.
- 28.10 A spring branch, 2 lks. wide, course S.
- 33.35 A spur, slopes S.; descend 67 ft. over broken SE. slope.