

DEPENDENT RESURVEY, PORTION OF N. BDY., T. 24 S., R. 3 W.

CHAINS

- A hemlock, 8 ins. diam., bears S. $18\frac{1}{4}^{\circ}$ E., 31 lks. dist., mkd. T 24 S R 3 W S 4 BT.
- A hemlock, 12 ins. diam., bears S. $70^{\circ}45'$ W., 56 lks. dist., mkd. T 24 S R 3 W S 5 BT.
- A yew, 18 ins. diam., bears N. $49\frac{1}{2}^{\circ}$ W., 97 lks. dist., mkd. T 23 S R 3 W S 32 BT.

Land, mountainous.
 Soil, sandy and rocky clay.
 Timber, fir, hemlock, cedar, yew, maple, alder and madrona.
 Undergrowth, vinemaple, salal, salmonberry, arrowwood, hazel, bracken, willow, rhododendron and huckleberry.

DEPENDENT RESURVEY, W. BDY., T. 24 S., R. 3 W.
 (Restoring the 1855 survey of Gordon and Gardner, the 1883 survey of Laban H. Wheeler, and the 1897 survey of Oscar F. Thiel.)

The cor. of Tps. 24 and 25 S., Rs. 3 and 4 W., is monumented with an iron post, 3 ins. diam., 8 ins. above ground, firmly set, mkd. and witnessed as described in the official record.

The geographic position of this corner is latitude $43^{\circ} 25' 58.48''$ N. and longitude $123^{\circ} 06' 26.13''$ W.

The observed magnetic declination at this corner is $20^{\circ}45'$ E.

N. $0^{\circ}27'$ E., bet. secs. 31 and 36.

Over open level bottom land.

- 4.90 Calapooya Creek, 50 lks. wide, course SW.; asc. 52 ft. over SE. slope, through heavy timber and dense undergrowth.
- 7.00 Top of ascent, bears NE. and SW.; thence over rolling bench.
- 13.80 A graded and graveled county road, bears N. 32° E. and S. 16° W.
- 14.65 A branch, 3 lks. wide, course S. 80° E.; ascend 101 ft. over broken SE. slope.
- 19.20 A spur, slopes E.; desc. 59 ft. over broken NE. slope.
- 28.25 A branch, 3 lks. wide, course SE.; asc. 253 ft. over broken SW. slope.
- 31.45 A graded dirt logging road, bears N. 40° W. and S. 25° E.
- 39.94 The $\frac{1}{4}$ sec. cor. of secs. 31 and 36, monumented by the county surveyor in 1903, with a cedar post, 30 ins. long, 4 ins. sq., firmly set, mkd. CS $\frac{1}{4}$ on W. face; from which a bearing tree mkd. by the county surveyor:
 A madrona, 22 ins. diam., bears N. 2° W., 59 lks. dist., with partial scribe marks visible on incompletely healed old blaze.

At the corner point

Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, with the county surveyor's marked stake deposited at the base, with brass cap mkd.

$\frac{1}{4}$
 S 36 | S 31
 1944
 1950